

---

**caldera**

**The MITRE Corporation**

**May 19, 2020**



## USAGE GUIDE:

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Getting started</b>                        | <b>3</b>  |
| 1.1      | Autonomous red-team engagements . . . . .     | 3         |
| 1.2      | Manual red-team engagements . . . . .         | 3         |
| 1.3      | Autonomous incident-response . . . . .        | 4         |
| 1.4      | Research on artificial intelligence . . . . . | 4         |
| <b>2</b> | <b>Learning the terminology</b>               | <b>5</b>  |
| 2.1      | What is an agent? . . . . .                   | 5         |
| 2.2      | What is a group? . . . . .                    | 5         |
| 2.3      | What is an ability? . . . . .                 | 5         |
| 2.4      | What is an adversary? . . . . .               | 7         |
| 2.5      | What is an operation? . . . . .               | 8         |
| 2.6      | What is a fact? . . . . .                     | 8         |
| 2.7      | What is a source? . . . . .                   | 9         |
| 2.8      | What is a rule? . . . . .                     | 9         |
| 2.8.1    | Subnets . . . . .                             | 10        |
| 2.9      | What is a planner? . . . . .                  | 10        |
| 2.9.1    | The <i>Batch</i> planner . . . . .            | 10        |
| 2.10     | What is a plugin? . . . . .                   | 10        |
| <b>3</b> | <b>Server configuration</b>                   | <b>11</b> |
| 3.1      | The existing default.yml . . . . .            | 11        |
| 3.2      | Adding your own config file . . . . .         | 12        |
| <b>4</b> | <b>Plugin library</b>                         | <b>13</b> |
| 4.1      | Sandcat (54ndc47) . . . . .                   | 13        |
| 4.1.1    | Deploy . . . . .                              | 13        |
| 4.1.2    | Options . . . . .                             | 13        |
| 4.2      | Mock . . . . .                                | 14        |
| 4.3      | Terminal . . . . .                            | 14        |
| 4.4      | Stockpile . . . . .                           | 15        |
| 4.5      | Response . . . . .                            | 15        |
| 4.6      | Compass . . . . .                             | 15        |
| 4.7      | Caltack . . . . .                             | 15        |
| 4.8      | SSL . . . . .                                 | 15        |
| 4.9      | Atomic . . . . .                              | 16        |
| 4.10     | GameBoard . . . . .                           | 16        |
| 4.11     | Human . . . . .                               | 16        |
| 4.12     | Training . . . . .                            | 16        |
| 4.13     | Access . . . . .                              | 16        |

|           |   |           |
|-----------|---|-----------|
| <b>5</b>  | <b>The REST API</b>   | <b>17</b> |
| 5.1       | /api/rest . . . . .   | 17        |
| 5.2       | Agents . . . . .  | 17        |
| 5.2.1     | DELETE . . . . .  | 17        |
| 5.2.2     | POST . . . . .  | 17        |
| 5.3       | Adversaries . . . . .   | 18        |
| 5.4       | Operations . . . . .  | 18        |
| 5.4.1     | DELETE . . . . .  | 18        |
| 5.4.2     | POST . . . . .  | 18        |
| 5.4.3     | PUT . . . . .   | 18        |
| 5.5       | /file/upload . . . . .  | 19        |
| 5.5.1     | Example . . . . .   | 19        |
| 5.6       | /file/download . . . . .  | 19        |
| 5.6.1     | Example . . . . .   | 19        |
| <b>6</b>  | <b>How to Build Plugins</b>   | <b>21</b> |
| 6.1       | Creating the structure . . . . .                                      | 21        |
| 6.2       | The <i>enable</i> function . . . . .                                  | 22        |
| 6.3       | Writing the code . . . . .  | 22        |
| 6.4       | Making it visual . . . . .  | 22        |
| <b>7</b>  | <b>How to Build Agents</b>  | <b>25</b> |
| 7.1       | Understanding contacts . . . . .                                      | 25        |
| 7.2       | Building an agent: HTTP contact . . . . .                             | 25        |
| 7.2.1     | Part #1 . . . . .   | 25        |
| 7.2.2     | Part #2 . . . . .   | 26        |
| 7.2.3     | Part #3 . . . . .   | 27        |
| 7.2.4     | Part #4 . . . . .   | 27        |
| <b>8</b>  | <b>How CALDERA makes decisions</b>                                    | <b>29</b> |
| <b>9</b>  | <b>Initial Access</b>   | <b>31</b> |
| 9.1       | Run an initial access technique . . . . .                             | 31        |
| 9.2       | Write an initial access ability . . . . .                             | 31        |
| 9.2.1     | Create a binary . . . . .   | 31        |
| 9.2.2     | Create an ability . . . . .   | 32        |
| 9.2.3     | Run the ability . . . . .   | 32        |
| <b>10</b> | <b>Install CALDERA offline</b>  | <b>33</b> |
| <b>11</b> | <b>Docker deployment</b>  | <b>35</b> |
| <b>12</b> | <b>CALDERA 2.0</b>  | <b>37</b> |
| 12.1      | Adversary Mode . . . . .  | 37        |
| 12.2      | Chain Mode . . . . .  | 37        |
| 12.3      | What's the long-term plan? . . . . .                                  | 38        |
| 12.4      | Why? . . . . .  | 38        |
| 12.5      | Gotchas . . . . .   | 38        |
| <b>13</b> | <b>Common problems</b>  | <b>39</b> |
| 13.1      | I'm getting an error starting the application! . . . . .              | 39        |
| 13.2      | I start an agent but cannot see it from the server! . . . . .         | 39        |
| 13.3      | I'm seeing issues in the browser - things don't seem right! . . . . . | 39        |
| 13.4      | I see a 404 when I try to download conf.yml! . . . . .                | 39        |
| 13.5      | I ran an adversary and it didn't do everything! . . . . .             | 40        |

|           |                                       |           |
|-----------|---------------------------------------|-----------|
| <b>14</b> | <b>app</b>                            | <b>41</b> |
| 14.1      | app.api namespace                     | 41        |
| 14.1.1    | Subpackages                           | 41        |
| 14.1.2    | Submodules                            | 41        |
| 14.1.3    | app.api.rest_api module               | 41        |
| 14.2      | app.contacts namespace                | 42        |
| 14.2.1    | Subpackages                           | 42        |
| 14.2.2    | Submodules                            | 42        |
| 14.2.3    | app.contacts.contact_gist module      | 42        |
| 14.2.4    | app.contacts.contact_html module      | 43        |
| 14.2.5    | app.contacts.contact_http module      | 43        |
| 14.2.6    | app.contacts.contact_tcp module       | 43        |
| 14.2.7    | app.contacts.contact_udp module       | 43        |
| 14.2.8    | app.contacts.contact_websocket module | 43        |
| 14.3      | app.learning namespace                | 44        |
| 14.3.1    | Submodules                            | 44        |
| 14.3.2    | app.learning.p_ip module              | 44        |
| 14.3.3    | app.learning.p_path module            | 44        |
| 14.4      | app.objects namespace                 | 44        |
| 14.4.1    | Subpackages                           | 44        |
| 14.4.2    | Submodules                            | 52        |
| 14.4.3    | app.objects.c_ability module          | 52        |
| 14.4.4    | app.objects.c_adversary module        | 53        |
| 14.4.5    | app.objects.c_agent module            | 54        |
| 14.4.6    | app.objects.c_obfuscator module       | 55        |
| 14.4.7    | app.objects.c_operation module        | 55        |
| 14.4.8    | app.objects.c_planner module          | 57        |
| 14.4.9    | app.objects.c_plugin module           | 57        |
| 14.4.10   | app.objects.c_schedule module         | 58        |
| 14.4.11   | app.objects.c_source module           | 58        |
| 14.5      | app.service namespace                 | 59        |
| 14.5.1    | Subpackages                           | 59        |
| 14.5.2    | Submodules                            | 64        |
| 14.5.3    | app.service.app_svc module            | 64        |
| 14.5.4    | app.service.auth_svc module           | 64        |
| 14.5.5    | app.service.contact_svc module        | 65        |
| 14.5.6    | app.service.data_svc module           | 66        |
| 14.5.7    | app.service.event_svc module          | 66        |
| 14.5.8    | app.service.file_svc module           | 67        |
| 14.5.9    | app.service.learning_svc module       | 68        |
| 14.5.10   | app.service.planning_svc module       | 68        |
| 14.5.11   | app.service.rest_svc module           | 69        |
| 14.6      | app.utility namespace                 | 70        |
| 14.6.1    | Submodules                            | 70        |
| 14.6.2    | app.utility.base_obfuscator module    | 70        |
| 14.6.3    | app.utility.base_object module        | 70        |
| 14.6.4    | app.utility.base_parser module        | 71        |
| 14.6.5    | app.utility.base_planning_svc module  | 71        |
| 14.6.6    | app.utility.base_service module       | 72        |
| 14.6.7    | app.utility.base_world module         | 73        |
| 14.6.8    | app.utility.config_generator module   | 74        |
| 14.6.9    | app.utility.file_decryptor module     | 74        |
| 14.6.10   | app.utility.payload_encoder module    | 74        |
| 14.6.11   | app.utility.rule_set module           | 75        |

|                              |           |
|------------------------------|-----------|
| <b>15 Indices and tables</b> | <b>77</b> |
| <b>Python Module Index</b>   | <b>79</b> |
| <b>Index</b>                 | <b>81</b> |

If you're new to CALDERA, this is a good place to start.





## GETTING STARTED

Before you start using CALDERA, you should determine how you'd like to use it. Because it is a cyber security framework, there are several ways you can utilize it - from offensive (red) to defensive (blue).

Here are the most common use-cases and basic instructions on how to proceed.

### 1.1 Autonomous red-team engagements

This is the original CALDERA use-case. You can use the framework to build a specific threat (adversary) profile and launch it in a network to see where you may be susceptible. This is good for testing defenses and training blue teams on how to detect threats.

To use this:

1. Log in as a red user
2. Click into the Sandcat plugin and deploy an agent on any compromised host
3. Review or build threat profiles in the Profiles tab. Hint: getting experienced red-team operators to build these profiles allows the blue team to re-run them anytime they want in the future.
4. Launch an operation against your agents using any threat profile

All built-in threat profiles are safe to use out-of-the-box.

### 1.2 Manual red-team engagements

You can use CALDERA to perform manual red-team assessments by leveraging the terminal plugin. This is good for replacing or appending existing offensive toolsets in a manual assessment, as the framework can be extended with any custom tools you may have.

To use this:

1. Log in as a red user
2. Click into the terminal plugin and deploy the Manx agent on any compromised host
3. Use the created sessions inside the terminal emulator to perform manual commands

## 1.3 Autonomous incident-response

You can leverage CALDERA to perform automated incident response on a given host. This is helpful for identifying TTPs that other security tools may not see or block.

To use this:

1. Log in as a blue user
2. Click into the Sandcat plugin and deploy an agent on any host
3. Review or build defender profiles in the Profiles tab
4. Launch an operation against your agents using any defender profile

Defender profiles utilize fact sources to determine good vs. bad on a given host.

## 1.4 Research on artificial intelligence

You can ignore all red/blue and security aspects of CALDERA and instead use it to test artificial intelligence and other decision-making algorithms.

To use this:

1. Enable the mock plugin and restart the server. Log in as a red user.
2. In the Campaigns -> Agents tab, review the simulated agents that have been spun up
3. Run an operation using any adversary against your simulated agents. Note how the operation runs non-deterministically. You can now go into the batch.py planning module and adjust the logic which makes decisions on what to do when to test out different theories.

## LEARNING THE TERMINOLOGY

### 2.1 What is an agent?

An agent is a simple software program - requiring no installation - which connects to CALDERA in order to get instructions. It then executes the instructions and sends the results back.

CALDERA includes a plugin, Sandcat (54ndc47), which is our default agent.

### 2.2 What is a group?

A group is a collection of agents connected to CALDERA. A group allows you to start an operation against multiple computers at the same time instead of one at a time.

When an agent is started, it automatically joins a generic group, `my_group`, but you can add or remove custom groups once an agent is connected.

During an operation, if an agent laterally moves to another computer, it will automatically become associated with the same group as the agent which started it.

### 2.3 What is an ability?

An ability is a specific ATT&CK technique implementation (procedure). Abilities are stored in YAML format and are loaded into CALDERA each time it starts.

All abilities are stored inside the Stockpile plugin, along with profiles which use them.

Here is a sample ability:

```
- id: 9a30740d-3aa8-4c23-8efa-d51215e8a5b9
  name: Scan WIFI networks
  description: View all potential WIFI networks on host
  tactic: discovery
  technique:
    attack_id: T1016
    name: System Network Configuration Discovery
  platforms:
    darwin:
      sh:
        command: |
          ./wifi.sh scan
        payload: wifi.sh
```

(continues on next page)

```
linux:
  sh:
    command: |
      ./wifi.sh scan
    payload: wifi.sh
windows:
  psh,pwsh:
    command: |
      .\wifi.ps1 -Scan
    payload: wifi.ps1
```

#### Things to note:

- Each ability has a random UUID id
- Each ability requires a name, description, ATT&CK tactic and technique information
- Each ability requires a platforms list, which should contain at least 1 block for a supported operating system (platform). Currently, abilities can be created for darwin, linux or windows.

For each platform, there should be a list of executors. Currently Darwin and Linux platforms can use sh and Windows can use psh (PowerShell), cmd (command prompt) or pwsh (open-source PowerShell core).

Each platform block consists of a:

- command (required)
- payload (optional)
- cleanup (optional)
- parsers (optional)
- requirements (optional)

**Command:** A command can be 1-line or many and should contain the code you would like the ability to execute. The command can (optionally) contain variables, which are identified as `#{variable}`. In the example above, there is one variable used, `#{files}`. A variable means that you are letting CALDERA fill in the actual contents. CALDERA has 3 global variables:

- `#{server}` references the FQDN of the CALDERA server itself. Because every agent may know the location of CALDERA differently, using the `#{server}` variable allows you to let the system determine the correct location of the server.
- `#{group}` is the group a particular agent is a part of. This variable is mainly useful for lateral movement, where your command can start an agent within the context of the agent starting it.
- `#{location}` is the location of the agent on the client file system.
- `#{paw}` is the unique identifier - or paw print - of the agent

Global variables can be identified quickly because they will be single words.

You can use these global variables freely and they will be filled in before the ability is used. Alternatively, you can write in your own variables and supply CALDERA with facts to fill them in.

**Payload:** A comma-separated list of files which the ability requires in order to run. In the windows executor above, the payload is `wifi.ps1`. This means, before the ability is used, the agent will download `wifi.ps1` from CALDERA. If the file already exists, it will not download it. You can store any type of file in the payload directories of any plugin.

Did you know that you can assign functions to execute on the server when specific payloads are requested for download? An example of this is the `sandcat.go` file. Check the `plugins/sandcat/hook.py` file to see how special payloads can be handled.

Payloads can be stored as regular files or you can xor (encode) them so the anti-virus on the server-side does not pick them up. To do this, run the `app/utility/payload_encoder.py` against the file to create an encoded version of it. Then store and reference the encoded payload instead of the original.

The `payload_encoder.py` file has a docstring which explains how to use the utility.

**Cleanup:** An instruction that will reverse the result of the command. This is intended to put the computer back into the state it was before the ability was used. For example, if your command creates a file, you can use the cleanup to remove the file. Cleanup commands run after an operation, in the reverse order they were created. Cleaning up an operation is also optional, which means you can start an operation and instruct it to skip all cleanup instructions.

Cleanup is not needed for abilities, like above, which download files through the payload block. Upon an operation completing, all payload files will be removed from the client (agent) computers.

**Parsers:** A list of parsing modules which can parse the output of the command into new facts. Interested in this topic? Check out [how CALDERA makes decisions](#) which goes into detail about parsers.

Abilities can also make use of two CALDERA REST API endpoints, file upload and download.

**Requirements:** Required relationships of facts that need to be established before this ability can be used.

## 2.4 What is an adversary?

An adversary is a collection of abilities.

The abilities inside an adversary can optionally be grouped into phases, which allows a user to choose which order they are executed. During an operation, each phase of the adversary is run in order. If there are multiple abilities in the same phase, CALDERA will determine which order to run them, based on the information it has gathered thus far in the operation. This decision making process is known as the planner. The main reason to group abilities into phases is if an ability from a latter phase depends on the fact output from a previous phase.

An adversary can contain abilities which can be used on any platform (operating system). As an operation runs an adversary, CALDERA will match each ability to each agent and only send the matching ones to the agent.

Adversaries can be built either through the GUI or by adding YML files into `data/adversaries/` which is in the Stockpile plugin.

An adversary YML file can include a `phases` section that lists the IDs of the abilities to execute in each phase. Here is an example of such an adversary:

```
id: 5d3e170e-f1b8-49f9-9ee1-c51605552a08
name: Collection
description: A collection adversary pack
phases:
  1:
    - 1f7ff232-ebf8-42bf-a3c4-657855794cfe #find company emails
    - d69e8660-62c9-431e-87eb-8cf6bd4e35cf #find ip addresses
    - 90c2efaa-8205-480d-8bb6-61d90dbaf81b #find sensitive files
    - 6469befa-748a-4b9c-a96d-f191fde47d89 #create staging dir
```

An adversary can be included in another adversary as a pack of abilities. This can be used to organize ability phases into groups for reuse by multiple adversaries. To do so, put the ID of another adversary in a phase just like an ability. In this case, CALDERA will expand and complete all the phases of that adversary before moving to the next phase.

An adversary YML file can also contain a `packs` section that contains the IDs of other adversaries. The ability phases from these adversary packs will be merged together into any existing phases, whether from the `phases` section itself or from other adversaries in the `packs` section. Here is an example using packs without phases:

```
id: de07f52d-9928-4071-9142-cb1d3bd851e8
name: Hunter
description: Discover host details and steal sensitive files
packs:
  - 0f4c3c67-845e-49a0-927e-90ed33c044e0
  - 1a98b8e6-18ce-4617-8cc5-e65a1a9d490e
```

Adversary YML files must contain either packs or phases, or both.

## 2.5 What is an operation?

An operation is started when you point an adversary at a group and have it run all capable abilities.

An operation can be started with a number of optional configurations:

- **Group:** Which collection of agents would you like to run against
- **Adversary:** Which adversary profile would you like to run
- **Run immediately:** Run the operation immediately or start in a paused state
- **Planner:** You can select which logic library - or planner - you would like to use.
- **Fact source:** You can attach a source of facts to an operation. This means the operation will start with “pre-knowledge” of the facts, which it can use to fill in variables inside the abilities.
- **Autonomous:** Run autonomously or manually. Manual mode will ask the operator to approve or discard each command.
- **Phases:** Run the adversary normally, abiding by phases, or smash all phases into a single one.
- **Auto-close:** Automatically close the operation when there is nothing left to do. Alternatively, keep the operation forever.
- **Obfuscators:** Select an obfuscator to encode each command with, before they are sent to the agents.
- **Jitter:** Agents normally check in with CALDERA every 60 seconds. Once they realize they are part of an active operation, agents will start checking in according to the jitter time, which is by default 2/8. This fraction tells the agents that they should pause between 2 and 8 seconds (picked at random each time an agent checks in) before using the next ability.
- **Visibility:** How visible should the operation be to the defense. Defaults to 51 because each ability defaults to a visibility of 50. Abilities with a higher visibility than the operation visibility will be skipped.

## 2.6 What is a fact?

A fact is an identifiable piece of information about a given computer. Facts are directly related to variables, which can be used inside abilities.

Facts are composed of a:

- **trait:** a 3-part descriptor which identifies the type of fact. An example is host.user.name. A fact with this trait tells me that it is a user name. This format allows you to specify the major (host) minor (user) and specific (name) components of each fact.
- **value:** any arbitrary string. An appropriate value for a host.user.name may be “Administrator” or “John”.

- **score**: an integer which associates a relative importance for the fact. Every fact, by default, gets a score of 1. If a `host.user.password` fact is important or has a high chance of success if used, you may assign it a score of 5. When an ability uses a fact to fill in a variable, it will use those with the highest scores first. If a fact has a score of 0, it will be blacklisted - meaning it cannot be used in the operation.

If a property has a major component = host (e.g., `host.user.name`) that fact will only be used by the host that collected it.

As hinted above, when CALDERA runs abilities, it scans the command and cleanup instructions for variables. When it finds one, it then looks at the facts it has and sees if it can replace the variables with matching facts (based on the property). It will then create new variants of each command/cleanup instruction for each possible combination of facts it has collected. Each variant will be scored based on the cumulative score of all facts inside the command. The highest scored variants will be executed first.

## 2.7 What is a source?

A source is a collection of facts that you have grouped together. A fact source can be applied to an operation when you start it, which gives the operation facts to fill in variables with.

## 2.8 What is a rule?

A Rule is a way of restricting or placing boundaries on CALDERA. Rules are directly related to facts and should be included in a fact sheet.

Rules act similar to firewall rules and have three key components: fact, action, and match

1. **Fact** specifies the name of the fact that the rule will apply to.
2. **Action** (ALLOW,DENY) will allow or deny the fact from use if it matches the rule.
3. **Match** regex rule on a fact's value to determine if the rule applies.

During an operation, the planning service matches each link against the rule-set, discarding it if any of the fact assignments in the link match a rule specifying DENY and keeping it otherwise. In the case that multiple rules match the same fact assignment, the last one listed will be given priority.

### Example

```
rules:
- action: DENY
  fact: file.sensitive.extension
  match: .*
- action: ALLOW
  fact: file.sensitive.extension
  match: txt
```

In this example only the txt file extension will be used. Note that the ALLOW action for txt supersedes the DENY for all, as the ALLOW rule is listed later in the policy. If the ALLOW rule was listed first, and the DENY rule second, then all values (including txt) for `file.sensitive.extension` would be discarded.

## 2.8.1 Subnets

Rules can also match against subnets.

### Subnet Example

```
- action: DENY
  fact: my.host.ip
  match: .*
- action: ALLOW
  fact: my.host.ip
  match: 10.245.112.0/24
```

In this example, the rules would permit CALDERA to only operate within the 10.245.112.1 to 10.245.112.254 range

## 2.9 What is a planner?

A planner is a module within CALDERA which contains logic for how a running operation should make decisions about which abilities to use and in what order.

Specifically, a planner's logic contains the decision making to execute a single phase of an operation. The core service - `operation_svc.py` - calls the planner for each phase of an adversary during an operation.

Planners are single module Python files. Planners utilize the core system's `planning_svc.py`, which has planning logic useful for various types of planners.

### 2.9.1 The *Batch* planner

CALDERA ships with a default planner, `batch`. During each phase of the operation, the batch planner loops through all agents (which are part of the operation's group) and sends each of them a list of all ability commands the planner thinks it can complete. This decision is based on the agent matching the operating system (execution platform) of the ability and the ability command having no unsatisfied variables. It then waits for each agent to complete their list of commands before moving on to the next phase.

## 2.10 What is a plugin?

CALDERA is built using a plugin architecture on top of the core system. Plugins are separate git repositories that plug new features into the core system. Each plugin resides in the `plugins` directory and is loaded into CALDERA by adding it to the `default.yml` file.

Each plugin contains a single `hook.py` file in its root directory. This file should contain an `initialize` function, which gets called automatically for each loaded plugin when CALDERA boots. The `initialize` function contains the plugin logic that is getting "plugged into" the core system. This function takes a single parameter:

1. **services**: a list of core services that live inside the core system.

A plugin can add nearly any new functionality/features to CALDERA by using the two objects above.



## SERVER CONFIGURATION

Caldera's configuration file is located at `conf/default.yml`.

### 3.1 The existing `default.yml`

The YAML configuration file contains all the configuration CALDERA requires to boot up. An example configuration file is below:

```
port: 8888
plugins:
  - sandcat
  - stockpile
  - compass
  - terminal
  - response
users:
  red:
    admin: admin
    red: admin
  blue:
    blue: admin
api_key: ADMIN123
exfil_dir: /tmp
reports_dir: /tmp
crypt_salt: REPLACE_WITH_RANDOM_VALUE
app.contact.http: http://0.0.0.0:8888
app.contact.tcp: 0.0.0.0:7010
app.contact.udp: 0.0.0.0:7011
app.contact.websocket: 0.0.0.0:7012
```

A few key things to note:

- **Port:** the port you serve CALDERA on
- **Plugins:** the list of all loaded `plugins`. A plugin must be in this list to be available when CALDERA is running. Adding a plugin to this list will result in that plugin's `hook.py` file getting called when CALDERA boots up.
- **Users:** the username/password credentials of all accounts you want to access the CALDERA login page. Users can either be in the red or blue group.
- **API\_KEY:** a password to use when accessing CALDERA programmatically.
- **Exfil\_dir:** the directory to use when an ability exfiltrates files from the agent, sending them back to CALDERA. Any file(s) posted to the `/file/upload` endpoint will end up in this directory.

- **Reports\_dir**: the directory to save all reports when the server shuts down
- **app.contact.http**: the http location you want HTTP agents (like Sandcat) to connect to.
- **app.contact.tcp**: the TCP socket you want reverse-shell agents (like Manx) to connect to.
- **app.contact.udp**: the UDP socket you want UDP agents (like Manx) to connect to
- **app.contact.websocket**: the websocket port agents can connect to

## 3.2 Adding your own config file

By default, CALDERA will use the `default.yml` file that is included with CALDERA, but this can be overridden by taking by creating your own `local.yml` file and saving it in the `conf/` directory. The name of the config file to use can also be specified with the `-E` flag when starting the server.

Caldera will choose the configuration file to use in the following order:

1. A config specified with the `-E` or `--environment` command-line options. For instance, if started with `python caldera.py -E foo`, CALDERA will load it's configuration from `conf/foo.yml`.
2. `conf/local.yml`: Caldera will prefer the local configuration file if no other options are specified.
3. `conf/default.yml`: If no config is specified with the `-E` option and it cannot find a `conf/local.yml` configuration file, CALDERA will use its default configuration options.

## PLUGIN LIBRARY

Here you'll get a run-down of all open-source plugins, all of which can be found in the `plugins/` directory as separate GIT repositories.

### 4.1 Sandcat (54ndc47)

The Sandcat plugin, otherwise known as 54ndc47, is the default agent that CALDERA ships with. 54ndc47 is written in GoLang for cross-platform compatibility.

54ndc47 agents require network connectivity to CALDERA at port 8888.

#### 4.1.1 Deploy

To deploy 54ndc47, use one of the built-in delivery commands which allows you to run the agent on any operating system. Each of these commands downloads the compiled 54ndc47 executable from CALDERA and runs it immediately. Find the commands on the Sandcat plugin tab.

Once the agent is running, it should show log messages when it beacons into CALDERA.

If you have GoLang installed on the CALDERA server, each time you run one of the delivery commands above, the agent will re-compile itself dynamically and it will change its source code so it gets a different file hash (MD5) and a random name that blends into the operating system. This will help bypass file-based signature detections.

#### 4.1.2 Options

When deploying a 54ndc47 agent, there are optional parameters you can use when you start the executable:

- **Server:** This is the location of CALDERA. The agent must have connectivity to this host/port.
- **Group:** This is the group name that you would like the agent to join when it starts. The group does not have to exist. A default group of `my_group` will be used if none is passed in.
- **v:** Use `-v` to see verbose output from sandcat. Otherwise, sandcat will run silently.

## Customizing Default Options & Execution Without CLI Options

It's possible to customize the default values of these options when pulling Sandcat from the CALDERA server. This is useful if you want to hide the parameters from the process tree. You can do this by passing the values in as headers instead of as parameters.

For example, the following will download a linux executable that will use `http://10.0.0.2:8888` as the server address instead of `http://localhost:8888`.

```
curl -sk -X POST -H 'file:sandcat.go' -H 'platform:linux' -H 'server:http://10.0.0.2:8888' http://localhost:8888/file/download > sandcat.sh
```

## 4.2 Mock

The Mock plugin adds a set of simulated agents to CALDERA and allows you to run complete operations without hooking any other computers up to your server.

These agents are created inside the `conf/agents.yml` file. They can be edited and you can create as many as you'd like. A sample agent looks like:

```
- paw: 1234
  username: darthvader
  host: deathstar
  group: simulation
  platform: windows
  location: C:\Users\Public
  enabled: True
  privilege: User
  c2: HTTP
  exe_name: sandcat.exe
  executors:
    - pwsh
    - psh
```

After you load the mock plugin and restart CALDERA, all simulated agents will appear as normal agents in the Chain plugin GUI and can be used in any operation.

## 4.3 Terminal

The terminal plugin adds reverse-shell capability to CALDERA, along with a TCP-based agent called Manx.

When this plugin is loaded, you'll get access to a new GUI page which allows you to drop reverse-shells on target hosts and interact manually with the hosts.

You can use the terminal emulator on the Terminal GUI page to interact with your sessions.

---

## 4.4 Stockpile

The stockpile plugin adds a few components to CALDERA:

- Abilities
- Adversaries
- Planner
- Facts

These components are all loaded through the `data/*` directory.

## 4.5 Response

The response plugin is an autonomous incident response plugin, which can fight back against adversaries on a compromised host.

## 4.6 Compass

Create visualizations to explore TTPs. Follow the steps below to create your own visualization:

1. Click 'Generate Layer'
2. Click '+' to open a new tab in the navigator
3. Select 'Open Existing Layer'
4. Select 'Upload from local' and upload the generated layer file

Compass leverages ATT&CK Navigator, for more information see: <https://github.com/mitre-attack/attack-navigator>

## 4.7 Caltack

The caltack plugin adds the public MITRE ATT&CK website to CALDERA. This is useful for deployments of CALDERA where an operator cannot access the Internet to reference the MITRE ATT&CK matrix.

After loading this plugin and restarting, the ATT&CK website is available from the CALDERA home page. Not all parts of the ATT&CK website will be available - but we aim to keep those pertaining to tactics and techniques accessible.

## 4.8 SSL

The SSL plugin adds HTTPS to CALDERA.

This plugin only works if CALDERA is running on a Linux or MacOS machine. It requires HaProxy (>= 1.8) to be installed prior to using it.

When this plugin has been loaded, CALDERA will start the HAProxy service on the machine and then serve CALDERA at `https://[YOUR_IP]:8443`, instead of the normal `https://[YOUR_IP]:8888`.

CALDERA will **only** be available at `https://[YOUR_IP]:8443` when using this plugin. All deployed agents should use the correct address to connect to CALDERA.

## 4.9 Atomic

The Atomic plugin imports all Red Canary Atomic tests from their open-source GitHub repository.

## 4.10 GameBoard

The GameBoard plugin allows you to monitor both red-and-blue team operations. The game tracks points for both sides and determines which one is “winning”.

## 4.11 Human

The Human plugin allows you to build “Humans” that will perform user actions on a target system as a means to obfuscate red actions by Caldera. Each human is built for a specific operating system and leverages the Chrome browser along with other native OS applications to perform a variety of tasks. Additionally, these humans can have various aspects of their behavior “tuned” to add randomization to the behaviors on the target system.

## 4.12 Training

This plugin allows a user to gain a “User Certificate” which proves their ability to use CALDERA. This is the first of several certificates planned in the future. The plugin takes you through a capture-the-flag style certification course, covering all parts CALDERA.

## 4.13 Access

This plugin allows you to task any agent with any ability from the database. It also allows you to conduct initial access attacks.

## THE REST API

All REST API functionality can be viewed in the `rest_api.py` module in the source code.

### 5.1 /api/rest

You can interact with all parts of CALDERA through the core REST API endpoint `/api/rest`. If you send requests to “localhost” - you are not required to pass a key header. If you send requests to `127.0.0.1` or any other IP addresses, the key header is required. You can set the API key in the `conf/default.yml` file. Some examples below will use the header, others will not, for example.

Any request to this endpoint must include an “index” as part of the request, which routes it to the appropriate object type.

Here are the available REST API functions:

### 5.2 Agents

#### 5.2.1 DELETE

Delete any agent.

```
curl -H "key:$API_KEY" -X DELETE http://localhost:8888/api/rest -d '{"index":"agents",  
↪ "paw": "$agent_paw"}'
```

#### 5.2.2 POST

View the abilities a given agent could execute.

```
curl -H "key:$API_KEY" -X POST localhost:8888/plugin/access/abilities -d '{"paw": "$PAW  
↪"}'
```

Execute a given ability against an agent, outside the scope of an operation.

```
curl -H "key:ADMIN123" -X POST localhost:8888/plugin/access/exploit -d '{"paw": "$PAW",  
↪ "ability_id": "$ABILITY_ID"}'````
```

You can optionally POST a facts dictionary with key/value pairs to fill in any variables the chosen ability requires.

```
{ "paw": "$PAW", "ability_id": "$ABILITY_ID", "facts": [{"trait": "username", "value": "admin"}  
↪, {"trait": "password", "value": "123"}]}
```

## 5.3 Adversaries

View all abilities for a specific adversary\_id (the UUID of the adversary).

```
curl -H 'KEY: ADMIN123' 'http://localhost:8888/api/rest' -H 'Content-Type:   
↪application/json' -d '{"index": "adversaries", "adversary_id": "$adversary_id"}'
```

View all abilities for all adversaries.

```
curl -H 'KEY: ADMIN123' 'http://localhost:8888/api/rest' -H 'Content-Type:   
↪application/json' -d '{"index": "adversaries"}'
```

## 5.4 Operations

### 5.4.1 DELETE

Delete any operation. Operation ID must be a integer.

```
curl -X DELETE http://localhost:8888/api/rest -d '{"index": "operations", "id": "  
↪$operation_id"}'
```

### 5.4.2 POST

Change the state of any operation. In addition to finished, you can also use: paused, run\_one\_link or running.

```
curl -X POST -H "KEY:ADMIN123" http://localhost:8888/api/rest -d '{"index": "operation  
↪", "op_id": 123, "state": "finished"}'
```

### 5.4.3 PUT

Create a new operation. All that is required is the operation name, similar to creating a new operation in the browser.

```
curl -X PUT -H "KEY:$KEY" http://127.0.0.1:8888/api/rest -d '{"index": "operations",  
↪ "name": "testoperation1"}'
```

Optionally, you can include:

1. group (defaults to empty string)
2. adversary\_id (defaults to empty string)
3. planner (defaults to *batch*)
4. source (defaults to *basic*)
5. jitter (defaults to 2/8)
6. obfuscator (defaults to *plain-text*)



7. visibility (defaults to 50)
8. autonomous (defaults to 1)
9. phases\_enabled (defaults to 1)
10. auto\_close (defaults to 0)

To learn more about these options, read the “What is an operation?” documentation section.

## 5.5 /file/upload

Files can be uploaded to CALDERA by POST’ing a file to the /file/upload endpoint. Uploaded files will be put in the `exfil_dir` location specified in the `default.yml` file.

### 5.5.1 Example

```
curl -F 'data=@path/to/file' http://localhost:8888/file/upload
```

## 5.6 /file/download

Files can be downloaded from CALDERA through the /file/download endpoint. This endpoint requires an HTTP header called “file” with the file name as the value. When a file is requested, CALDERA will look inside each of the payload directories listed in the `local.yml` file until it finds a file matching the name.

Files can also be downloaded indirectly through the [payload block of an ability](#).

Additionally, the [54ndc47 plugin](#) delivery commands utilize the file download endpoint to drop the agent on a host

### 5.6.1 Example

```
curl -X POST -H "file:wifi.sh" http://localhost:8888/file/download > wifi.sh
```



## HOW TO BUILD PLUGINS

Building your own plugin allows you to add custom functionality to CALDERA.

A plugin can be nearly anything, from a RAT/agent (like 54ndc47) to a new GUI or a collection of abilities that you want to keep in “closed-source”.

Plugins are stored in the plugins directory. If a plugin is also listed in the local.yml file, it will be loaded into CALDERA each time the server starts. A plugin is loaded through its hook.py file, which is “hooked” into the core system via the server.py (main) module.

When constructing your own plugins, you should avoid importing modules from the core code base, as these can change. There are two exceptions to this rule

1. The services dict() passed to each plugin can be used freely. Only utilize the public functions on these services however. These functions will be defined on the services’ corresponding interface.
2. Any c\_object that implements the FirstClassObjectInterface. Only call the functions on this interface, as the others are subject to changing.

### 6.1 Creating the structure

Start by creating a new directory called “abilities” in CALDERA’s plugins directory. In this directory, create a hook.py file and ensure it looks like this:

```
name = 'Abilities'  
description = 'A sample plugin for demonstration purposes'  
address = None  
  
async def enable(services):  
    pass
```

The name should always be a single word, the description a phrase, and the address should be None, unless your plugin exposes new GUI pages. Our example plugin will be called “abilities”.

## 6.2 The *enable* function

The enable function is what gets hooked into CALDERA at boot time. This function accepts one parameter:

1. **services:** a list of core services that CALDERA creates at boot time, which allow you to interact with the core system in a safe manner.

Core services can be found in the `app/services` directory.

## 6.3 Writing the code

Now it's time to fill in your own enable function. Let's start by appending a new REST API endpoint to the server. When this endpoint is hit, we will direct the request to a new class (`AbilityFetcher`) and function (`get_abilities`). The full `hook.py` file now looks like:

```
from aiohttp import web

name = 'Abilities'
description = 'A sample plugin for demonstration purposes'
address = None

async def enable(services):
    app = services.get('app_svc').application
    fetcher = AbilityFetcher(services)
    app.router.add_route('*', '/get/abilities', fetcher.get_abilities)

class AbilityFetcher:

    def __init__(self, services):
        self.services = services

    async def get_abilities(self, request):
        abilities = await self.services.get('data_svc').locate('abilities')
        return web.json_response(dict(abilities=[a.display for a in abilities]))
```

Now that our initialize function is filled in, let's add the plugin to the `default.yml` file and restart CALDERA. Once running, in a browser or via cURL, navigate to `127.0.0.1:8888/get/abilities`. If all worked, you should get a JSON response back, with all the abilities within CALDERA.

## 6.4 Making it visual

Now we have a usable plugin, but we want to make it more visually appealing.

Start by creating a "templates" directory inside your plugin directory (`abilities`). Inside the templates directory, create a new file called `abilities.html`. Ensure the content looks like:

```
<div id="abilities-new-section" class="section-profile">
  <div class="row">
    <div class="topleft duk-icon"></div>
    <div class="column section-border" style="flex:25%;text-align:left;
    ↪padding:15px;">
```

(continues on next page)

(continued from previous page)

```

        <h1 style="font-size:70px;margin-top:-20px;">Abilities</h1>
    </div>
    <div class="column" style="flex:75%;padding:15px;text-align: left">
        <div>
            {% for a in abilities %}
                <pre style="color:white">{{ a }}</pre>
                <hr>
            {% endfor %}
        </div>
    </div>
</div>

```

Then, back in your hook.py file, let's fill in the address variable and ensure we return the new abilities.html page when a user requests 127.0.0.1/get/abilities. Here is the full hook.py:

```

from aiohttp_jinja2 import template, web

name = 'Abilities'
description = 'A sample plugin for demonstration purposes'
address = '/plugin/abilities/gui'

async def enable(services):
    app = services.get('app_svc').application
    fetcher = AbilityFetcher(services)
    app.router.add_route('*', '/plugin/abilities/gui', fetcher.splash)
    app.router.add_route('GET', '/get/abilities', fetcher.get_abilities)

class AbilityFetcher:
    def __init__(self, services):
        self.services = services
        self.auth_svc = services.get('auth_svc')

    async def get_abilities(self, request):
        abilities = await self.services.get('data_svc').locate('abilities')
        return web.json_response(dict(abilities=[a.display for a in abilities]))

    @template('abilities.html')
    async def splash(self, request):
        await self.auth_svc.check_permissions(request)
        abilities = await self.services.get('data_svc').locate('abilities')
        return(dict(abilities=[a.display for a in abilities]))

```

Restart CALDERA and navigate to the home page. Be sure to run `server.py` with the `--fresh` flag to flush the previous object store database.

You should see a new “abilities” tab at the top, clicking on this should navigate you to the new abilities.html page you created.



## HOW TO BUILD AGENTS

Building your own agent is a way to create a unique - or undetectable - footprint on compromised machines. Our default agent, 54ndc47, is a representation of what an agent can do. This agent is written in GoLang and offers an extensible collection of command-and-control (C2) protocols, such as communicating over HTTP or GitHub Gist.

You can extend 54ndc47 by adding your own C2 protocols in place or you can follow this guide to create your own agent from scratch.

### 7.1 Understanding contacts

Agents are processes which are deployed on compromised hosts and connect with the C2 server periodically for instructions. An agent connects to the server through a *contact*, which is a specific connection point on the server.

Each contact is defined in an independent Python module and is registered with the `contact_svc` when the server starts.

There are currently several built-in contacts available: `http`, `tcp`, `udp` and `websocket`.

### 7.2 Building an agent: HTTP contact

Start by getting a feel for the HTTP endpoint, which are located in the `contacts/contact_http.py` module.

```
POST /beacon
```

#### 7.2.1 Part #1

Start by writing a POST request to the `/beacon` endpoint.

In your agent code, create a flat JSON dictionary of key/value pairs and ensure the following properties are included as keys. Add values which correlate to the host your agent will be running on. Note - all of these properties are optional - but you should aim to cover as many as you can.

If you don't include a platform and executors then the server will never provide instructions to the agent, as it won't know which ones are valid to send.

- **server:** The location (IP or FQDN) of the C2 server
- **platform:** The operating system
- **host:** The hostname of the machine
- **username:** The username running the agent
- **architecture:** The architecture of the host

- **executors:** A list of executors allowed on the host
- **privilege:** The privilege level of the agent process, either User or Elevated
- **pid:** The process identifier of the agent
- **location:** The location of the agent on disk
- **exe\_name:** The name of the agent binary file

At this point, you are ready to make a POST request with the profile to the /beacon endpoint. You should get back:

1. The recommended number of seconds to sleep before sending the next beacon
2. The recommended number of seconds (watchdog) to wait before killing the agent, once the server is unreachable (0 means infinite)
3. A list of instructions - base64 encoded.

```
profile=$(echo '{"server":"http://127.0.0.1:8888","platform":"darwin","executors":["sh
↵"]}' | base64)
curl -s -X POST -d $profile localhost:8888/beacon | base64 --decode
...{"paw": "dcoify", sleep": 59, "watchdog": 0, "instructions": "[...]"}

```

The paw property returned back from the server represents a unique identifier for your new agent. Each time you call the /beacon endpoint without this paw, a new agent will be created on the server - so you should ensure that future beacons include it.

You can now navigate to the CALDERA UI, click into the agents tab and view your new agent.

## 7.2.2 Part #2

Now it's time to execute the instructions.

Looking at the previous response, you can see each instruction contains:

- **id:** The link ID associated to the ability
- **sleep:** A recommended pause to take after running this instruction
- **command:** A base64 encoded command to run
- **executor:** The executor to run the command under
- **timeout:** How long to let the command run before timing it out
- **payload:** A payload file name which must be downloaded before running the command, if applicable

Now, you'll want to revise your agent to loop through all the instructions, executing each command and POSTing the response back to the /beacon endpoint. You should pause after running each instruction, using the sleep time provided inside the instruction.

```
data=$(echo '{"result":{"id":$id, "output":$output, "status": $status, "pid":$pid}}'
↵| base64)
curl -s -X POST -d $data localhost:8888/beacon
sleep $instruction_sleep

```

The POST details inside the result are as follows:

- **id:** the ID of the instruction you received
- **output:** the base64 encoded output from running the instruction
- **status:** the status code from running the instruction. If unsure, put 0.



- **pid**: the process identifier the instruction ran under. If unsure, put 0.

Once all instructions are run, the agent should sleep for the specified time in the beacon before calling the /beacon endpoint again. This process should repeat forever.

### 7.2.3 Part #3

Inside each instruction, there is an optional *payload* property that contains a filename of a file to download before running the instruction. To implement this, add a file download capability to your agent, directing it to the /file/download endpoint to retrieve the file:

```
payload='some_file_name.txt'
curl -X POST -H "file:$payload" http://localhost:8888/file/download > some_file_name.
↪txt
```

### 7.2.4 Part #4

You should implement the watchdog configuration. This property, passed to the agent in every beacon, contains the number of seconds to allow a dead beacon before killing the agent.



## HOW CALDERA MAKES DECISIONS

CALDERA makes decisions using parsers, which are optional blocks inside an ability.

Let's look at an example snippet of an ability that uses a parser:

```
darwin:
  sh:
    command: |
      find /Users -name '*.#{file.sensitive.extension}' -type f -not -path '*/\.*
↪ ' 2>/dev/null
    parsers:
      plugins.stockpile.app.parsers.basic:
        - source: host.file.sensitive
          edge: has_extension
          target: file.sensitive.extension
```

A parser is identified by the module which contains the code to parse the command's output. The parser can contain:

**Source** (required): A fact to create for any matches from the parser

**Edge** (optional): A relationship between the source and target. This should be a string.

**Target** (optional): A fact to create which the source connects too.

In the above example, the output of the command will be sent through the `plugins.stockpile.app.parsers.basic` module, which will create a relationship for every found file.



## INITIAL ACCESS

CALDERA allows for easy initial access attacks, by leveraging the Access plugin. This guide will walk you through how to fire off an initial access attack, as well as how to build your own.

### 9.1 Run an initial access technique

Start by deploying an agent locally. This agent will be your “assistant”. It will execute any attack you feed it. You could alternatively deploy the agent remotely, which will help mask where your initial access attacks are originating.

From the Access plugin, select your agent and either the initial access tactic or any pre-ATT&CK tactic. This will filter the abilities. Select any ability within your chosen tactic.

Once selected, a pop-up box will show you details about the ability. You’ll need to fill in values for any properties your selected ability requires. Click OK when done.

Finally, click to run the ability against your selected agent. The ability will be in one of 3 states: IN-PROGRESS, SUCCESS or FAILED. If it is in either of the latter two states, you can view the logs from the executed ability by clicking on the star.

### 9.2 Write an initial access ability

You can easily add new initial access or pre-ATT&CK abilities yourself.

#### 9.2.1 Create a binary

You can use an existing binary or write your own - in any language - to act as your payload. The binary itself should contain the code to execute your attack. It can be as simple or complex as you’d like. It should accept parameters for any dynamic behaviors. At minimum, you should require a parameter for “target”, which would be your intended IP address, FQDN or other target that your attack will run against.

As an example, look at the scanner.sh binary used for conducting a simple NMAP scan:

```
#!/bin/bash

echo '[+] Starting basic NMAP scan'
nmap -Pn $1
echo '[+] Complete with module'
```

This binary simply echos a few log statements and runs an NMAP scan against the first parameter (i.e., the target) passed to it.

## 9.2.2 Create an ability

With your binary at hand, you can now create a new ability YML file inside the Access plugin (plugins/access/data/abilities/\*). Select the correct tactic directory (or create one if one does not exist). Here is what the YML file looks like for the scanner.sh binary:

```
---
- id: 567eaaba-94cc-4a27-83f8-768e5638f4e1
  name: NMAP scan
  description: Scan an external host for open ports and services
  tactic: technical-information-gathering
  technique:
    name: Conduct active scanning
    attack_id: T1254
  platforms:
    darwin,linux:
      sh:
        command: |
          ./scanner.sh #{target.ip}
        timeout: 300
        payloads:
          - scanner.sh
```

This is the same format that is used for other CALDERA abilities, so refer to the “Learning the terminology” doc page for a run-through of all the fields.

## 9.2.3 Run the ability

With your ability YML file loaded, restart CALDERA and head to the Access plugin to run it.

## INSTALL CALDERA OFFLINE

To install CALDERA on a server without internet access, `pip` can be used to download the CALDERA dependencies from a machine with internet access. Once the dependencies are downloaded, they can be copied to the offline machine and installed.

The internet machine's platform and python version should match offline server. For example, if the the offline target machine runs Python 3.6 on CentOS 7, then Python3.6 and CentOS 7 should be used to perform the packaging to minimize problems.

```
git clone --recursive https://github.com/mitre/caldera.git
mkdir caldera/python_deps
pip download -r caldera/requirements.txt --dest caldera/python_deps
```

The `caldera` directory can now be copied to the offline server via whatever means are convenient (`scp` if there's connectivity, sneaker.net, etc)

Once the `caldera` directory has been copied to the offline machine the dependencies can be installed with `pip`.

```
pip install -r caldera/requirements.txt --no-index --find-links caldera/python_deps
```

CALDERA can then be started as usual:

```
cd caldera
python server.py
```





## DOCKER DEPLOYMENT

If you wish to run CALDERA from a Docker container, execute the commands below.

1. Build a container from the latest changes.

```
docker build . -t caldera:server
```

1. Run the docker CALDERA server

```
docker run -p 7010:7010 -p 7011:7011 -p 7012:7012 -p 8888:8888 caldera:server
```



## CALDERA 2.0

In April 2019, the CALDERA team pushed out several large changes to the core CALDERA code-base, effectively creating a “new” version of CALDERA: CALDERA 2.0. This new version of CALDERA featured a much more modular plugin-based architecture, many bug-fixes, a new GUI, and most importantly, the introduction of two operating modes: **adversary mode** and **chain mode**.

### 12.1 Adversary Mode

Adversary mode is the classic CALDERA capability. Functionally, the mode is the same as it was when first released in 2017 – it still runs fully automated, end-to-end operations using a dynamic planner – although now it has some internal optimizations, bug fixes, and a different GUI. Setup and requirements for this mode are also largely the same as when first released: you must install the CAgent software on each endpoint you want to test (Windows only), pointing the agent back to the CALDERA server to run the operation. Installing the agent is now much simpler, and can be done via a PowerShell script that’s displayed on the adversary mode page. From an architecture perspective, the adversary mode functionality is now entirely encapsulated in the “adversary” plugin; without loading this plugin, the functionality will be absent.

### 12.2 Chain Mode

Chain mode is the new operating mode for CALDERA, and was first introduced in the “2.0” release in mid 2019. This mode was designed to allow users to orchestrate/string together atomic unit tests into larger attack sequences; unlike adversary mode, chain mode was originally not designed to be dynamic, and each operation was to be run explicitly sans any variables in commands. Chain mode’s relatively simple use case enabled us to design it with a much smaller footprint, requiring only simple agents to execute commands as dictated by the CALDERA server; unlike adversary mode, chain mode leverages a single agent (not an agent + a RAT), and only needs a single agent to be connected to the CALDERA server to test a network (as opposed to each endpoint needing to have CAgent installed). Generally speaking, chain mode has significantly less overhead than adversary mode, albeit at the cost of some of adversary mode’s dynamism.

## 12.3 What's the long-term plan?

Long term, we hope to subsume adversary mode's capabilities into chain mode by adding dynamism to chain mode operations, encoding input and output for each chain mode action in a way that's similar to (though more intuitive than) the way actions are encoded in adversary mode.

## 12.4 Why?

After releasing the first version of chain mode, we realized that this new functionality was significantly easier to stand up than our initial adversary mode release; we've found that many people struggling to run adversary mode operations are typically struggling with that mode's dependencies/encoding. Moreover, chain mode's light overhead makes it easier to extend with new actions, allowing us to more readily encode more of the ATT&CK matrix than we could with adversary mode. We believe that shifting our operations to something lighter-weight will allow more people to use CALDERA for more use cases.

## 12.5 Gotchas

Our CALDERA 2.0 push came without much fanfare – or documentation! We've discovered that there are some minor pain points when first using this new version:

- Adversary mode is disabled by default. To use adversary mode, download the adversary mode plugin and make the appropriate changes to the main CALDERA local.conf file.
- Existing documentation on CALDERA is largely out to date. In particular, our page on readthedocs needs to be updated. Much of that information still pertains to adversary mode, although stuff that talks more broadly about CALDERA is somewhat dated.
- CALDERA's GUI is now significantly different; don't worry if it doesn't look the way it does in other public material!
- Adversary mode still only supports execution on Windows machines. Chain mode by contrast has support for Windows, Linux, or Mac.

## COMMON PROBLEMS

### 13.1 I'm getting an error starting the application!

1. You likely have a misalignment between the core code and the plugin repositories. This is typically caused by doing a “git pull” on one of the repositories and not the others. If you see this error, you should re-clone the latest stable version of CALDERA (recursively, of course).
2. Another common reason for this is running CALDERA from < Python 3.6.1.

### 13.2 I start an agent but cannot see it from the server!

1. Check that the firewall is open, allowing network connections, between the remote computer running the agent and the server itself.
2. Ensure you are serving CALDERA on all interfaces (0.0.0.0).
3. If you are running the agent on Windows, our default agent assumes it is a 64-bit system. If you are running 32-bit, you'll need to recompile the Windows agent to use it.

### 13.3 I'm seeing issues in the browser - things don't seem right!

1. Are you using Chrome or Safari? These are the only supported/tested browsers. All other ones are use-at-your-own-risk.

### 13.4 I see a 404 when I try to download conf.yml!

1. The conf.yml file is only relevant to pre-CALDERA 2.0. You should go to the README page and follow the instructions to run one of the missions.

## 13.5 I ran an adversary and it didn't do everything!

1. Check each ability on the adversary profile. It should show an icon for which operating system it runs on. Match this up with the operating systems of your agents. These are the only abilities an operation will attempt to run.
2. Look at each ability command. If there is a variable inside - shown by `{ }` syntax - the ability will need to be “unlocked” by another ability, in a prior phase, before it can run.

The following section contains information intended to help developers understand the inner workings of the CALDERA adversary emulation tool, CALDERA plugins, or new tools that interface with the CALDERA server.

## 14.1 app.api namespace

### 14.1.1 Subpackages

app.api.packs namespace

Submodules

app.api.packs.advanced module

```
class app.api.packs.advanced.AdvancedPack (services)
    Bases: app.utility.base_world.BaseWorld
    async enable ()
```

app.api.packs.campaign module

```
class app.api.packs.campaign.CampaignPack (services)
    Bases: app.utility.base_world.BaseWorld
    async enable ()
```

### 14.1.2 Submodules

#### 14.1.3 app.api.rest\_api module

```
class app.api.rest_api.RestApi (services)
    Bases: app.utility.base_world.BaseWorld
    async download_file (request)
    async enable ()
    async landing (request)
    async login (request)
    async logout (request)
    async rest_core (**params)
```

```
async upload_file (request)
async validate_login (request)
```

## 14.2 app.contacts namespace

### 14.2.1 Subpackages

app.contacts.handles namespace

Submodules

app.contacts.handles.h\_beacon module

```
class app.contacts.handles.h_beacon.Handle (tag)
    Bases: object
    async static run (message, services, caller)
```

### 14.2.2 Submodules

#### 14.2.3 app.contacts.contact\_gist module

```
class app.contacts.contact_gist.Gist (services)
    Bases: app.utility.base_world.BaseWorld
    async get_beacons ()
        Retrieve all GIST beacons for a particular api key :return: the beacons
    async get_results ()
        Retrieve all GIST posted results for a this C2's api key :return:
    async gist_operation_loop ()
    async handle_beacons (beacons)
        Handles various beacons types (beacon and results)
    retrieve_config ()
    async start ()
    async valid_config ()
app.contacts.contact_gist.api_access (func)
```



#### 14.2.4 app.contacts.contact\_html module

```
class app.contacts.contact_html.Html (services)
    Bases: app.utility.base_world.BaseWorld

    async start ()
```

#### 14.2.5 app.contacts.contact\_http module

```
class app.contacts.contact_http.Http (services)
    Bases: app.utility.base_world.BaseWorld

    async start ()
```

#### 14.2.6 app.contacts.contact\_tcp module

```
class app.contacts.contact_tcp.Tcp (services)
    Bases: app.utility.base_world.BaseWorld

    async operation_loop ()
    async start ()

class app.contacts.contact_tcp.TcpSessionHandler (services, log)
    Bases: app.utility.base_world.BaseWorld

    async accept (reader, writer)
    async refresh ()
    async send (session_id, cmd)
```

#### 14.2.7 app.contacts.contact\_udp module

```
class app.contacts.contact_udp.Handler (services)
    Bases: asyncio.protocols.DatagramProtocol

    datagram_received (data, addr)
        Called when some datagram is received.

class app.contacts.contact_udp.Udp (services)
    Bases: app.utility.base_world.BaseWorld

    async start ()
```

#### 14.2.8 app.contacts.contact\_websocket module

```
class app.contacts.contact_websocket.Handler (services)
    Bases: object

    async handle (socket, path)

class app.contacts.contact_websocket.WebSocket (services)
    Bases: app.utility.base_world.BaseWorld

    async start ()
```

## 14.3 app.learning namespace

### 14.3.1 Submodules

#### 14.3.2 app.learning.p\_ip module

```
class app.learning.p_ip.Parser
    Bases: object
    parse (blob)
```

#### 14.3.3 app.learning.p\_path module

```
class app.learning.p_path.Parser
    Bases: object
    parse (blob)
```

## 14.4 app.objects namespace

### 14.4.1 Subpackages

#### app.objects.interfaces namespace

##### Submodules

#### app.objects.interfaces.i\_object module

```
class app.objects.interfaces.i_object.FirstClassObjectInterface
    Bases: abc.ABC
    abstract store (ram)
    abstract property unique
```

#### app.objects.secondclass namespace

##### Submodules

#### app.objects.secondclass.c\_fact module

```
class app.objects.secondclass.c_fact.Fact (trait, value=None, score=1, col-
                                           lected_by=None, technique_id=None)
    Bases: app.utility.base_object.BaseObject
    escaped (executor)
    load_schema = <FactSchema (many=False)>
    schema = <FactSchema (many=False)>
    property unique
```

```

class app.objects.secondclass.c_fact.FactSchema (*, only: Union[Sequence[str],
Set[str]] = None, exclude:
Union[Sequence[str], Set[str]]
= (), many: bool = False, con-
text: Dict = None, load_only:
Union[Sequence[str], Set[str]] = (),
dump_only: Union[Sequence[str],
Set[str]] = (), partial: Union[bool,
Sequence[str], Set[str]] = False,
unknown: str = None)

```

Bases: `marshmallow.schema.Schema`

`build_fact` (*data*, *\*\*\_*)

`opts` = `<marshmallow.schema.SchemaOpts object>`

### app.objects.secondclass.c\_instruction module

```

class app.objects.secondclass.c_instruction.Instruction (id, command, executor,
payloads=None, sleep=0,
timeout=60)

```

Bases: `app.utility.base_object.BaseObject`

`property display`

`schema` = `<InstructionSchema (many=False)>`

```

class app.objects.secondclass.c_instruction.InstructionSchema (*, only:
Union[Sequence[str],
Set[str]] =
None, exclude:
Union[Sequence[str],
Set[str]] = (),
many: bool
= False, con-
text: Dict =
None, load_only:
Union[Sequence[str],
Set[str]] =
(), dump_only:
Union[Sequence[str],
Set[str]] =
(), partial:
Union[bool,
Sequence[str],
Set[str]] = False,
unknown: str =
None)

```

Bases: `marshmallow.schema.Schema`

`build_instruction` (*data*, *\*\*\_*)

`opts` = `<marshmallow.schema.SchemaOpts object>`

**app.objects.secondclass.c\_link module**

```
class app.objects.secondclass.c_link.Link(command, paw, ability, status=-3, score=0,
                                         jitter=0, cleanup=0, id=None, pin=0,
                                         host=None)
```

```
Bases: app.utility.base_object.BaseObject
```

```
apply_id(host)
```

```
can_ignore()
```

```
display_schema = <LinkSchema(many=False)>
```

```
load_schema = <LinkSchema(many=False)>
```

```
async parse(operation, result)
```

```
property pin
```

```
schema = <LinkSchema(many=False)>
```

```
property states
```

```
property unique
```

```
class app.objects.secondclass.c_link.LinkSchema(*, only: Union[Sequence[str],
Set[str]] = None, exclude:
Union[Sequence[str], Set[str]]
= (), many: bool = False, con-
text: Dict = None, load_only:
Union[Sequence[str], Set[str]] = (),
dump_only: Union[Sequence[str],
Set[str]] = (), partial: Union[bool,
Sequence[str], Set[str]] = False,
unknown: str = None)
```

```
Bases: marshmallow.schema.Schema
```

```
class Meta
```

```
Bases: object
```

```
unknown = 'exclude'
```

```
build_link(data, **_)
```

```
opts = <marshmallow.schema.SchemaOpts object>
```

```
prepare_link(data, **_)
```

**app.objects.secondclass.c\_parser module**

```
class app.objects.secondclass.c_parser.Parser(module, parserconfigs)
```

```
Bases: app.utility.base_object.BaseObject
```

```
schema = <ParserSchema(many=False)>
```

```
property unique
```

```

class app.objects.secondclass.c_parser.ParserSchema (*, only: Union[Sequence[str],
Set[str]] = None, exclude:
Union[Sequence[str], Set[str]]
= (), many: bool = False, con-
text: Dict = None, load_only:
Union[Sequence[str],
Set[str]] = (), dump_only:
Union[Sequence[str], Set[str]]
= (), partial: Union[bool, Se-
quence[str], Set[str]] = False,
unknown: str = None)

Bases: marshmallow.schema.Schema

build_parser (data, **_)

fix_relationships (parser, **_)

opts = <marshmallow.schema.SchemaOpts object>

prepare_parser (data, **_)

```

#### app.objects.secondclass.c\_parserconfig module

```

class app.objects.secondclass.c_parserconfig.ParserConfig (source, edge=None,
target=None,
**kwargs)

```

Bases: *app.utility.base\_object.BaseObject*

**schema** = <ParserConfigSchema (many=False)>

```

class app.objects.secondclass.c_parserconfig.ParserConfigSchema (*, only:
Union[Sequence[str],
Set[str]] =
None, exclude:
Union[Sequence[str],
Set[str]] = (),
many: bool =
False, context:
Dict = None,
load_only:
Union[Sequence[str],
Set[str]] = (),
dump_only:
Union[Sequence[str],
Set[str]] =
(), partial:
Union[bool,
Sequence[str],
Set[str]] =
False, un-
known: str =
None)

```

Bases: marshmallow.schema.Schema

**class Meta**

Bases: object

**unknown** = 'include'

```

build_parserconfig (data, **_)
check_edge_target (in_data, **_)
opts = <marshmallow.schema.SchemaOpts object>
remove_nones (data, **_)

```

### app.objects.secondclass.c\_relationship module

```

class app.objects.secondclass.c_relationship.Relationship (source, edge=None,
                                                         target=None, score=1)

```

Bases: *app.utility.base\_object.BaseObject*

**property** display

**classmethod** from\_json (json)

**load\_schema** = <RelationshipSchema (many=False)>

**schema** = <RelationshipSchema (many=False)>

**property** unique

```

class app.objects.secondclass.c_relationship.RelationshipSchema (*, only:
                                                                Union[Sequence[str],
                                                                Set[str]] =
                                                                None, exclude:
                                                                Union[Sequence[str],
                                                                Set[str]] = (),
                                                                many: bool =
                                                                False, context:
                                                                Dict = None,
                                                                load_only:
                                                                Union[Sequence[str],
                                                                Set[str]] = (),
                                                                dump_only:
                                                                Union[Sequence[str],
                                                                Set[str]] =
                                                                (), partial:
                                                                Union[bool,
                                                                Sequence[str],
                                                                Set[str]] =
                                                                False, un-
                                                                known: str =
                                                                None)

```

Bases: *marshmallow.schema.Schema*

**build\_relationship** (data, \*\*\_)

**opts** = <marshmallow.schema.SchemaOpts object>

**app.objects.secondclass.c\_requirement module**

```

class app.objects.secondclass.c_requirement.Requirement (module, relation-ship_match)
    Bases: app.utility.base_object.BaseObject
    schema = <RequirementSchema (many=False)>
    property unique

class app.objects.secondclass.c_requirement.RequirementSchema (*, only: Union[Sequence[str], Set[str]] = None, exclude: Union[Sequence[str], Set[str]] = (), many: bool = False, context: Dict = None, load_only: Union[Sequence[str], Set[str]] = (), dump_only: Union[Sequence[str], Set[str]] = (), partial: Union[bool, Sequence[str], Set[str]] = False, unknown: str = None)
    Bases: marshmallow.schema.Schema
    build_requirement (data, **_)
    opts = <marshmallow.schema.SchemaOpts object>

```

**app.objects.secondclass.c\_result module**

```

class app.objects.secondclass.c_result.Result (id, output, pid=0, status=0)
    Bases: app.utility.base_object.BaseObject
    schema = <ResultSchema (many=False)>

class app.objects.secondclass.c_result.ResultSchema (*, only: Union[Sequence[str], Set[str]] = None, exclude: Union[Sequence[str], Set[str]] = (), many: bool = False, context: Dict = None, load_only: Union[Sequence[str], Set[str]] = (), dump_only: Union[Sequence[str], Set[str]] = (), partial: Union[bool, Sequence[str], Set[str]] = False, unknown: str = None)
    Bases: marshmallow.schema.Schema

```

```

build_result (data, **_)
opts = <marshmallow.schema.SchemaOpts object>

```

### app.objects.secondclass.c\_rule module

```

class app.objects.secondclass.c_rule.Rule (action, trait, match='.*')
    Bases: app.utility.base_object.BaseObject
    schema = <RuleSchema (many=False)>

```

```

class app.objects.secondclass.c_rule.RuleActionField (*, default: Any = <marshmallow.missing>, missing: Any = <marshmallow.missing>, data_key: str = None, attribute: str = None, validate: Union[Callable[[Any], Any], Iterable[Callable[[Any], Any]]] = None, required: bool = False, allow_none: bool = None, load_only: bool = False, dump_only: bool = False, error_messages: Dict[str, str] = None, **metadata)

```

Bases: marshmallow.fields.Field

Custom field to handle the RuleAction Enum.

```

class app.objects.secondclass.c_rule.RuleSchema (*, only: Union[Sequence[str], Set[str]] = None, exclude: Union[Sequence[str], Set[str]] = (), many: bool = False, context: Dict = None, load_only: Union[Sequence[str], Set[str]] = (), dump_only: Union[Sequence[str], Set[str]] = (), partial: Union[bool, Sequence[str], Set[str]] = False, unknown: str = None)

```

Bases: marshmallow.schema.Schema

```

build_rule (data, **_)
opts = <marshmallow.schema.SchemaOpts object>

```

### app.objects.secondclass.c\_variation module

```

class app.objects.secondclass.c_variation.Variation (description, command)
    Bases: app.utility.base_object.BaseObject
    property command
    schema = <VariationSchema (many=False)>

```



```

class app.objects.secondclass.c_variation.VariationSchema (*,
                                                         only:
                                                         Union[Sequence[str],
                                                         Set[str]] =
                                                         None, exclude:
                                                         Union[Sequence[str],
                                                         Set[str]] = (), many:
                                                         bool = False, context:
                                                         Dict = None, load_only:
                                                         Union[Sequence[str],
                                                         Set[str]] = (),
                                                         dump_only:
                                                         Union[Sequence[str],
                                                         Set[str]] = (), par-
                                                         tial: Union[bool,
                                                         Sequence[str], Set[str]]
                                                         = False, unknown: str
                                                         = None)

Bases: marshmallow.schema.Schema
build_variation (data, **_)
opts = <marshmallow.schema.SchemaOpts object>

```

#### app.objects.secondclass.c\_visibility module

```

class app.objects.secondclass.c_visibility.Visibility
  Bases: app.utility.base_object.BaseObject
  MAX_SCORE = 100
  MIN_SCORE = 1
  apply (adjustment)
  property display
  schema = <VisibilitySchema (many=False)>
  property score

```

```

class app.objects.secondclass.c_visibility.VisibilitySchema (*,
                                                           only:
                                                           Union[Sequence[str],
                                                           Set[str]] =
                                                           None, exclude:
                                                           Union[Sequence[str],
                                                           Set[str]] = (), many:
                                                           bool = False,
                                                           context: Dict =
                                                           None, load_only:
                                                           Union[Sequence[str],
                                                           Set[str]] = (),
                                                           dump_only:
                                                           Union[Sequence[str],
                                                           Set[str]] = (), partial:
                                                           Union[bool,
                                                           Sequence[str],
                                                           Set[str]] = False,
                                                           unknown: str =
                                                           None)

Bases: marshmallow.schema.Schema

build_visibility (data, **_)

opts = <marshmallow.schema.SchemaOpts object>

```

## 14.4.2 Submodules

### 14.4.3 app.objects.c\_ability module

```

class app.objects.c_ability.Ability (ability_id, tactic=None, technique_id=None, technique=None, name=None, test=None, description=None, cleanup=None, executor=None, platform=None, payloads=None, parsers=None, requirements=None, privilege=None, timeout=60, repeatable=False, buckets=None, access=None, variations=None, language=None, code=None, build_target=None, **kwargs)

Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.utility.base_object.BaseObject

HOOKS = {}

RESERVED = {'payload': '#{payload}'}

async add_bucket (bucket)

display_schema = <AbilitySchema (many=False)>

replace_cleanup (encoded_cmd, payload)

schema = <AbilitySchema (many=False)>

store (ram)

property test

property unique

async which_plugin ()

```

```

class app.objects.c_ability.AbilitySchema (*, only: Union[Sequence[str], Set[str]] = None,
                                          exclude: Union[Sequence[str], Set[str]] = (),
                                          many: bool = False, context: Dict = None,
                                          load_only: Union[Sequence[str], Set[str]] = (),
                                          dump_only: Union[Sequence[str], Set[str]] =
                                          (), partial: Union[bool, Sequence[str], Set[str]]
                                          = False, unknown: str = None)

Bases: marshmallow.schema.Schema

build_ability (data, **_)

opts = <marshmallow.schema.SchemaOpts object>

```

#### 14.4.4 app.objects.c\_adversary module

```

class app.objects.c_adversary.Adversary (adversary_id, name, description,
                                         atomic_ordering)
Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.
utility.base_object.BaseObject

has_ability (ability)

schema = <AdversarySchema (many=False)>

store (ram)

property unique

async which_plugin ()

class app.objects.c_adversary.AdversarySchema (*, only: Union[Sequence[str], Set[str]]
= None, exclude: Union[Sequence[str],
Set[str]] = (), many: bool = False,
context: Dict = None, load_only:
Union[Sequence[str], Set[str]] = (),
dump_only: Union[Sequence[str],
Set[str]] = (), partial: Union[bool, Se-
quence[str], Set[str]] = False, unknown:
str = None)

Bases: marshmallow.schema.Schema

build_adversary (data, **_)

fix_id (adversary, **_)

opts = <marshmallow.schema.SchemaOpts object>

phase_to_atomic_ordering (adversary, **_)
    Convert legacy adversary phases to atomic ordering

```

### 14.4.5 app.objects.c\_agent module

```

class app.objects.c_agent.Agent (sleep_min, sleep_max, watchdog, platform='unknown',
                                server='unknown', host='unknown', username='unknown',
                                architecture='unknown', group='red', location='unknown',
                                pid=0, ppid=0, trusted=True, executors=(), privilege='User',
                                exe_name='unknown', contact='unknown', paw=None,
                                proxy_receivers=None)

Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.
utility.base_object.BaseObject

RESERVED = {'agent_paw': '#{paw}', 'exe_name': '#{exe_name}', 'group': '#{group}',
all_facts ()

async bootstrap (data_svc)

async calculate_sleep ()

async capabilities (ability_set)

property display_name

async gui_modification (**kwargs)

async heartbeat_modification (**kwargs)

async kill ()

load_schema = <AgentSchema (many=False)>

privileged_to_run (ability)

replace (encoded_cmd, file_svc)

schema = <AgentSchema (many=False)>

store (ram)

async task (abilities, facts=())

property unique

class app.objects.c_agent.AgentFieldsSchema (*, only: Union[Sequence[str], Set[str]]
= None, exclude: Union[Sequence[str], Set[str]] = (), many: bool = False,
context: Dict = None, load_only: Union[Sequence[str], Set[str]] = (),
dump_only: Union[Sequence[str], Set[str]] = (), partial: Union[bool, Sequence[str],
Set[str]] = False, unknown: str = None)

Bases: marshmallow.schema.Schema

opts = <marshmallow.schema.SchemaOpts object>

remove_nulls (in_data, **_)

class app.objects.c_agent.AgentSchema (*, only: Union[Sequence[str], Set[str]] = None,
exclude: Union[Sequence[str], Set[str]] = (),
many: bool = False, context: Dict = None,
load_only: Union[Sequence[str], Set[str]] = (),
dump_only: Union[Sequence[str], Set[str]] = (),
partial: Union[bool, Sequence[str], Set[str]] = False,
unknown: str = None)

Bases: app.objects.c_agent.AgentFieldsSchema

```

```

build_agent (data, **_)
opts = <marshmallow.schema.SchemaOpts object>

```

#### 14.4.6 app.objects.c\_obfuscator module

```

class app.objects.c_obfuscator.Obfuscator (name, description, module)
  Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.
utility.base_object.BaseObject

  display_schema = <ObfuscatorSchema (many=False)>

  load (agent)

  schema = <ObfuscatorSchema (many=False)>

  store (ram)

  property unique

class app.objects.c_obfuscator.ObfuscatorSchema (*, only: Union[Sequence[str],
Set[str]] = None, exclude:
Union[Sequence[str], Set[str]] = (), many: bool = False, con-
text: Dict = None, load_only:
Union[Sequence[str], Set[str]] = (),
dump_only: Union[Sequence[str],
Set[str]] = (), partial: Union[bool,
Sequence[str], Set[str]] = False,
unknown: str = None)

  Bases: marshmallow.schema.Schema

  opts = <marshmallow.schema.SchemaOpts object>

```

#### 14.4.7 app.objects.c\_operation module

```

class app.objects.c_operation.Operation (name, agents, adversary, id=None, jitter='2/8',
source=None, planner=None, state='running',
autonomous=True, obfuscator='plain-text',
group=None, auto_close=True, visibility=50,
access=None)

  Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.
utility.base_object.BaseObject

class Reason
  Bases: enum.Enum

  An enumeration.

  EXECUTOR = 1

  FACT_DEPENDENCY = 2

  OP_RUNNING = 4

  PLATFORM = 0

  PRIVILEGE = 3

  UNTRUSTED = 5

```

```

async active_agents ()
add_link (link)
all_facts ()
all_relationships ()
async apply (link)
async close (services)
async get_active_agent_by_paw (paw)
has_fact (trait, value)
has_link (link_id)
async is_closeable ()
async is_finished ()
link_status ()
async report (file_svc, data_svc, output=False, redacted=False)
async run (services)
schema = <OperationSchema (many=False)>
set_start_details ()
property states
store (ram)
property unique
async update_operation (services)
async wait_for_completion ()
async wait_for_links_completion (link_ids)
    Wait for started links to be completed :param link_ids: :return: None
class app.objects.c_operation.OperationSchema (*, only: Union[Sequence[str], Set[str]]
    = None, exclude: Union[Sequence[str], Set[str]] = (), many: bool = False,
    context: Dict = None, load_only: Union[Sequence[str], Set[str]] = (),
    dump_only: Union[Sequence[str], Set[str]] = (), partial: Union[bool, Sequence[str], Set[str]] = False,
    unknown: str = None)

    Bases: marshmallow.schema.Schema
build_planner (data, **_)
opts = <marshmallow.schema.SchemaOpts object>

```

### 14.4.8 app.objects.c\_planner module

```

class app.objects.c_planner.Planner(planner_id, name, module, params, stop-
    ping_conditions=None, description=None, ig-
    nore_enforcement_modules=())
    Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.
    utility.base_object.BaseObject
    display_schema = <PlannerSchema(many=False)>
    schema = <PlannerSchema(many=False)>
    store (ram)
    property unique
    async which_plugin()

class app.objects.c_planner.PlannerSchema(*, only: Union[Sequence[str], Set[str]] = None,
    exclude: Union[Sequence[str], Set[str]] = (),
    many: bool = False, context: Dict = None,
    load_only: Union[Sequence[str], Set[str]] = (),
    dump_only: Union[Sequence[str], Set[str]] =
    (), partial: Union[bool, Sequence[str], Set[str]]
    = False, unknown: str = None)
    Bases: marshmallow.schema.Schema
    build_planner(data, **_)
    opts = <marshmallow.schema.SchemaOpts object>

```

### 14.4.9 app.objects.c\_plugin module

```

class app.objects.c_plugin.Plugin(name='virtual', description=None, address=None, en-
    abled=False, data_dir=None, access=None)
    Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.
    utility.base_object.BaseObject
    async destroy(services)
    display_schema = <PluginSchema(many=False)>
    async enable(services)
    async expand(services)
    async load_plugin()
    schema = <PluginSchema(many=False)>
    store (ram)
    property unique

class app.objects.c_plugin.PluginSchema(*, only: Union[Sequence[str], Set[str]] = None,
    exclude: Union[Sequence[str], Set[str]] = (),
    many: bool = False, context: Dict = None,
    load_only: Union[Sequence[str], Set[str]] = (),
    dump_only: Union[Sequence[str], Set[str]] = (),
    partial: Union[bool, Sequence[str], Set[str]] =
    False, unknown: str = None)
    Bases: marshmallow.schema.Schema

```

```

build_plugin (data, **_)
opts = <marshmallow.schema.SchemaOpts object>

```

#### 14.4.10 app.objects.c\_schedule module

```

class app.objects.c_schedule.Schedule (name, schedule, task)
  Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.
  utility.base_object.BaseObject

```

```

schema = <ScheduleSchema (many=False)>

```

```

store (ram)

```

```

property unique

```

```

class app.objects.c_schedule.ScheduleSchema (*, only: Union[Sequence[str], Set[str]]
  = None, exclude: Union[Sequence[str],
  Set[str]] = (), many: bool = False,
  context: Dict = None, load_only:
  Union[Sequence[str], Set[str]] = (),
  dump_only: Union[Sequence[str], Set[str]]
  = (), partial: Union[bool, Sequence[str],
  Set[str]] = False, unknown: str = None)

```

```

  Bases: marshmallow.schema.Schema

```

```

opts = <marshmallow.schema.SchemaOpts object>

```

#### 14.4.11 app.objects.c\_source module

```

class app.objects.c_source.Adjustment (ability_id, trait, value, offset)

```

```

  Bases: tuple

```

```

property ability_id
  Alias for field number 0

```

```

property offset
  Alias for field number 3

```

```

property trait
  Alias for field number 1

```

```

property value
  Alias for field number 2

```

```

class app.objects.c_source.AdjustmentSchema (*, only: Union[Sequence[str], Set[str]]
  = None, exclude: Union[Sequence[str],
  Set[str]] = (), many: bool = False,
  context: Dict = None, load_only:
  Union[Sequence[str], Set[str]] = (),
  dump_only: Union[Sequence[str], Set[str]]
  = (), partial: Union[bool, Sequence[str],
  Set[str]] = False, unknown: str = None)

```

```

  Bases: marshmallow.schema.Schema

```

```

build_adjustment (data, **_)

```

```

opts = <marshmallow.schema.SchemaOpts object>

```



```

class app.objects.c_source.Source (id, name, facts, relationships=(), rules=(), adjustments=())
    Bases: app.objects.interfaces.i_object.FirstClassObjectInterface, app.
            utility.base_object.BaseObject

    display_schema = <SourceSchema (many=False)>

    schema = <SourceSchema (many=False)>

    store (ram)

    property unique

class app.objects.c_source.SourceSchema (*, only: Union[Sequence[str], Set[str]] = None,
            exclude: Union[Sequence[str], Set[str]] = (),
            many: bool = False, context: Dict = None,
            load_only: Union[Sequence[str], Set[str]] = (),
            dump_only: Union[Sequence[str], Set[str]] = (),
            partial: Union[bool, Sequence[str], Set[str]] =
            False, unknown: str = None)

    Bases: marshmallow.schema.Schema

    build_source (data, **_)

    fix_adjustments (in_data, **_)

    opts = <marshmallow.schema.SchemaOpts object>

```

## 14.5 app.service namespace

### 14.5.1 Subpackages

#### app.service.interfaces namespace

##### Submodules

#### app.service.interfaces.i\_app\_svc module

```

class app.service.interfaces.i_app_svc.AppServiceInterface
    Bases: abc.ABC

    abstract find_link (unique)
        Locate a given link by its unique property :param unique: :return:

    abstract find_op_with_link (link_id)
        Locate an operation with the given link ID :param link_id: :return: Operation or None

    abstract load_plugin_expansions (plugins)

    abstract load_plugins (plugins)
        Store all plugins in the data store :return:

    abstract register_contacts ()

    abstract resume_operations ()
        Resume all unfinished operations :return: None

    abstract retrieve_compiled_file (name, platform)

```

**abstract run\_scheduler** (*identifier*)

Kick off all scheduled jobs, as their schedule determines :return:

**abstract start\_sniffer\_untrusted\_agents** ()

Cyclic function that repeatedly checks if there are agents to be marked as untrusted :return: None

**abstract teardown** ()

### app.service.interfaces.i\_auth\_svc module

**class** app.service.interfaces.i\_auth\_svc.**AuthServiceInterface**

Bases: abc.ABC

**abstract apply** (*app, users*)

Set up security on server boot :param app: :param users: :return: None

**abstract check\_permissions** (*group, request*)

Check if a request is allowed based on the user permissions :param group: :param request: :return: None

**abstract get\_permissions** (*request*)

**abstract login\_user** (*request*)

Kick off all scheduled jobs, as their schedule determines :return:

**abstract static logout\_user** (*request*)

Log the user out :param request: :return: None

### app.service.interfaces.i\_contact\_svc module

**class** app.service.interfaces.i\_contact\_svc.**ContactServiceInterface**

Bases: abc.ABC

**abstract build\_filename** ()

**abstract handle\_heartbeat** ()

Accept all components of an agent profile and save a new agent or register an updated heartbeat. :return: the agent object, instructions to execute

**abstract register** (*contact*)

Register a virtual subclass of an ABC.

Returns the subclass, to allow usage as a class decorator.

### app.service.interfaces.i\_data\_svc module

**class** app.service.interfaces.i\_data\_svc.**DataServiceInterface**

Bases: abc.ABC

**abstract apply** (*collection*)

Add a new collection to RAM :param collection: :return:

**abstract static destroy** ()

Clear out all data :return:

**abstract load\_data** (*plugins*)

Non-blocking read all the data sources to populate the object store :return: None

**abstract locate** (*object\_name, match*)  
 Find all c\_objects which match a search. Return all c\_objects if no match. :param object\_name: :param match: dict() :return: a list of c\_object types

**abstract reload\_data** (*plugins*)  
 Blocking read all the data sources to populate the object store :return: None

**abstract remove** (*object\_name, match*)  
 Remove any c\_objects which match a search :param object\_name: :param match: dict() :return:

**abstract restore\_state** ()

**abstract save\_state** ()  
 Accept all components of an agent profile and save a new agent or register an updated heartbeat. :return: the agent object, instructions to execute

**abstract store** (*c\_object*)  
 Accept any c\_object type and store it (create/update) in RAM :param c\_object: :return: a single c\_object

### app.service.interfaces.i\_event\_svc module

**class** app.service.interfaces.i\_event\_svc.**EventServiceInterface**  
 Bases: abc.ABC

**abstract fire\_event** (*event, \*\*callback\_kwargs*)  
 Fire an event :param event: The event topic and (optional) subtopic, separated by a '/' :param callback\_kwargs: Any additional parameters to pass to the event handler :return: None

**abstract observe\_event** (*event, callback*)  
 Register an event handler :param event: The event topic and (optional) subtopic, separated by a '/' :param callback: The function that will handle the event :return: None

### app.service.interfaces.i\_file\_svc module

**class** app.service.interfaces.i\_file\_svc.**FileServiceInterface**  
 Bases: abc.ABC

**abstract add\_special\_payload** (*name, func*)  
 Call a special function when specific payloads are downloaded :param name: :param func: :return:

**abstract compile\_go** (*platform, output, src\_file, arch, ldflags, cflags, buildmode, build\_dir, loop*)  
 Dynamically compile a go file :param platform: :param output: :param src\_file: :param arch: Compile architecture selection (defaults to AMD64) :param ldflags: A string of ldflags to use when building the go executable :param cflags: A string of CFLAGS to pass to the go compiler :param buildmode: GO compiler buildmode flag :param build\_dir: The path to build should take place in :return:

**abstract create\_exfil\_sub\_directory** (*dir\_name*)

**abstract find\_file\_path** (*name, location*)  
 Find the location on disk of a file by name. :param name: :param location: :return: a tuple: the plugin the file is found in & the relative file path

**abstract get\_file** (*headers*)  
 Retrieve file :param headers: headers dictionary. The *file* key is REQUIRED. :type headers: dict or dict-equivalent :return: File contents and optionally a display\_name if the payload is a special payload :raises: KeyError if file key is not provided, FileNotFoundError if file cannot be found

**abstract get\_payload\_name\_from\_uuid** (*payload*)

**abstract read\_file** (*name, location*)

Open a file and read the contents :param name: :param location: :return: a tuple (file\_path, contents)

**abstract read\_result\_file** (*link\_id, location*)

Read a result file. If file encryption is enabled, this method will return the plaintext content. :param link\_id: The id of the link to return results from. :param location: The path to results directory. :return:

**abstract save\_file** (*filename, payload, target\_dir*)

**abstract save\_multipart\_file\_upload** (*request, target\_dir*)

Accept a multipart file via HTTP and save it to the server :param request: :param target\_dir: The path of the directory to save the uploaded file to.

**abstract write\_result\_file** (*link\_id, output, location*)

Writes the results of a link execution to disk. If file encryption is enabled, the results file will contain ciphertext. :param link\_id: The link id of the result being written. :param output: The content of the link's output. :param location: The path to the results directory. :return:

### app.service.interfaces.i\_learning\_svc module

**class** app.service.interfaces.i\_learning\_svc.**LearningServiceInterface**

Bases: abc.ABC

**abstract static add\_parsers** (*directory*)

**abstract build\_model** ()

The model is a static set of all variables used inside all ability commands This can be used to determine which facts - when found together - are more likely to be used together :return:

**abstract learn** (*facts, link, blob*)

### app.service.interfaces.i\_planning\_svc module

**class** app.service.interfaces.i\_planning\_svc.**PlanningServiceInterface**

Bases: abc.ABC

**abstract generate\_and\_trim\_links** (*agent, operation, abilities, trim*)

**abstract get\_cleanup\_links** (*operation, agent*)

For a given operation, create all cleanup links. If agent is supplied, only return cleanup links for that agent. :param operation: :param agent: :return: None

**abstract get\_links** (*operation, agent, trim, planner, stopping\_conditions*)

For an operation and agent combination, create links (that can be executed). When no agent is supplied, links for all agents are returned :param operation: :param agent: :param trim: call trim\_links() on list of links before returning :param planner: :param stopping\_conditions: :return: a list of links

**abstract static sort\_links** (*self, links*)

Sort links by their score then by the order they are defined in an adversary profile

**app.service.interfaces.i\_rest\_svc module**

```
class app.service.interfaces.i_rest_svc.RestServiceInterface
```

```
Bases: abc.ABC
```

```
abstract apply_potential_link (link)
```

```
abstract construct_agents_for_group (group)
```

```
abstract create_operation (access, data)
```

```
abstract create_schedule (access, data)
```

```
abstract delete_ability (data)
```

```
abstract delete_adversary (data)
```

```
abstract delete_agent (data)
```

```
abstract delete_operation (data)
```

```
abstract display_objects (object_name, data)
```

```
abstract display_operation_report (data)
```

```
abstract display_result (data)
```

```
abstract download_contact_report (contact)
```

```
abstract find_abilities (paw)
```

```
abstract get_link_pin (json_data)
```

```
abstract get_potential_links (op_id, paw)
```

```
abstract list_payloads ()
```

```
abstract persist_ability (data)
```

```
abstract persist_adversary (data)
```

Save a new adversary from either the GUI or REST API. This writes a new YML file into the core data/ directory. :param data: :return: the ID of the created adversary

```
abstract persist_source (data)
```

```
abstract task_agent_with_ability (paw, ability_id, facts)
```

```
abstract update_agent_data (data)
```

```
abstract update_chain_data (data)
```

```
abstract update_config (data)
```

```
abstract update_operation (op_id, state, autonomous)
```

```
abstract update_planner (data)
```

Update a new planner from either the GUI or REST API with new stopping conditions. This overwrites the existing YML file. :param data: :return: the ID of the created adversary

## 14.5.2 Submodules

### 14.5.3 app.service.app\_svc module

```
class app.service.app_svc.AppService (application)
    Bases: app.service.interfaces.i_app_svc.AppServiceInterface, app.utility.
    base_service.BaseService

    property errors

    async find_link (unique)
        Locate a given link by its unique property :param unique: :return:

    async find_op_with_link (link_id)
        Locate an operation with the given link ID :param link_id: :return: Operation or None

    async load_plugin_expansions (plugins=())

    async load_plugins (plugins)
        Store all plugins in the data store :return:

    async register_contacts ()

    async resume_operations ()
        Resume all unfinished operations :return: None

    async retrieve_compiled_file (name, platform)

    async run_scheduler ()
        Kick off all scheduled jobs, as their schedule determines :return:

    async start_sniffer_untrusted_agents ()
        Cyclic function that repeatedly checks if there are agents to be marked as untrusted :return: None

    async teardown (main_config_file='default')

    async validate_requirement (requirement, params)

    async validate_requirements ()

class app.service.app_svc.Error (name, msg)
    Bases: tuple

    property msg
        Alias for field number 1

    property name
        Alias for field number 0
```

### 14.5.4 app.service.auth\_svc module

```
class app.service.auth_svc.AuthService
    Bases: app.service.interfaces.i_auth_svc.AuthServiceInterface, app.utility.
    base_service.BaseService

    class User (username, password, permissions)
        Bases: tuple

        property password
            Alias for field number 1
```

**property permissions**

Alias for field number 2

**property username**

Alias for field number 0

**async apply** (*app, users*)

Set up security on server boot :param app: :param users: :return: None

**async check\_permissions** (*group, request*)

Check if a request is allowed based on the user permissions :param group: :param request: :return: None

**async get\_permissions** (*request*)**async login\_user** (*request*)

Log a user in and save the session :param request: :return: the response/location of where the user is trying to navigate

**async static logout\_user** (*request*)

Log the user out :param request: :return: None

**class** app.service.auth\_svc.**DictionaryAuthorizationPolicy** (*user\_map*)

Bases: aiohttp\_security.abc.AbstractAuthorizationPolicy

**async authorized\_userid** (*identity*)

Retrieve authorized user id. Return the user\_id of the user identified by the identity or 'None' if no user exists related to the identity.

**async permits** (*identity, permission, context=None*)

Check user permissions. Return True if the identity is allowed the permission in the current context, else return False.

app.service.auth\_svc.**check\_authorization** (*func*)Authorization Decorator This requires that the calling class have *self.auth\_svc* set to the authentication service.app.service.auth\_svc.**for\_all\_public\_methods** (*decorator*)

class decorator – adds decorator to all public methods

## 14.5.5 app.service.contact\_svc module

**class** app.service.contact\_svc.**ContactService**Bases: *app.service.interfaces.i\_contact\_svc.ContactServiceInterface*, *app.utility.base\_service.BaseService***async build\_filename** ()**async get\_contact** (*name*)**async handle\_heartbeat** (*\*\*kwargs*)**async register** (*contact*)

Register a virtual subclass of an ABC.

Returns the subclass, to allow usage as a class decorator.

app.service.contact\_svc.**report** (*func*)

## 14.5.6 app.service.data\_svc module

**class** app.service.data\_svc.**DataService**

Bases: *app.service.interfaces.i\_data\_svc.DataServiceInterface*, *app.utility.base\_service.BaseService*

**async apply** (*collection*)

Add a new collection to RAM :param collection: :return:

**async static destroy** ()

Clear out all data :return:

**async load\_data** (*plugins=()*)

Non-blocking read all the data sources to populate the object store :return: None

**async locate** (*object\_name, match=None*)

Find all c\_objects which match a search. Return all c\_objects if no match. :param object\_name: :param match: dict() :return: a list of c\_object types

**async reload\_data** (*plugins=()*)

Blocking read all the data sources to populate the object store :return: None

**async remove** (*object\_name, match*)

Remove any c\_objects which match a search :param object\_name: :param match: dict() :return:

**async restore\_state** ()

Restore the object database

### Returns

**async save\_state** ()

Accept all components of an agent profile and save a new agent or register an updated heartbeat. :return: the agent object, instructions to execute

**async store** (*c\_object*)

Accept any c\_object type and store it (create/update) in RAM :param c\_object: :return: a single c\_object

## 14.5.7 app.service.event\_svc module

**class** app.service.event\_svc.**EventService**

Bases: *app.service.interfaces.i\_event\_svc.EventServiceInterface*, *app.utility.base\_service.BaseService*

**async fire\_event** (*event, \*\*callback\_kwargs*)

Fire an event :param event: The event topic and (optional) subtopic, separated by a '/' :param callback\_kwargs: Any additional parameters to pass to the event handler :return: None

**async handle\_exceptions** (*awaitable*)

**async observe\_event** (*event, callback*)

Register an event handler :param event: The event topic and (optional) subtopic, separated by a '/' :param callback: The function that will handle the event :return: None



## 14.5.8 app.service.file\_svc module

**class** app.service.file\_svc.**FileSvc**

Bases: *app.service.interfaces.i\_file\_svc.FileServiceInterface, app.utility.base\_service.BaseService*

**async add\_special\_payload** (*name, func*)

Call a special function when specific payloads are downloaded

**Parameters**

- **name** –
- **func** –

**Returns**

**async compile\_go** (*platform, output, src\_file, arch='amd64', ldflags='-s -w', cflags='', buildmode='', build\_dir='.', loop=None*)

Dynamically compile a go file :param platform: :param output: :param src\_file: :param arch: Compile architecture selection (defaults to AMD64) :param ldflags: A string of ldflags to use when building the go executable :param cflags: A string of CFLAGS to pass to the go compiler :param buildmode: GO compiler buildmode flag :param build\_dir: The path to build should take place in :return:

**async create\_exfil\_sub\_directory** (*dir\_name*)

**async find\_file\_path** (*name, location=""*)

Find the location on disk of a file by name. :param name: :param location: :return: a tuple: the plugin the file is found in & the relative file path

**async get\_file** (*headers*)

Retrieve file :param headers: headers dictionary. The *file* key is REQUIRED. :type headers: dict or dict-equivalent :return: File contents and optionally a display\_name if the payload is a special payload :raises: KeyError if file key is not provided, FileNotFoundError if file cannot be found

**get\_payload\_name\_from\_uid** (*payload*)

**async read\_file** (*name, location='payloads'*)

Open a file and read the contents :param name: :param location: :return: a tuple (file\_path, contents)

**read\_result\_file** (*link\_id, location='data/results'*)

Read a result file. If file encryption is enabled, this method will return the plaintext content. :param link\_id: The id of the link to return results from. :param location: The path to results directory. :return:

**async save\_file** (*filename, payload, target\_dir*)

**async save\_multipart\_file\_upload** (*request, target\_dir*)

Accept a multipart file via HTTP and save it to the server :param request: :param target\_dir: The path of the directory to save the uploaded file to.

**write\_result\_file** (*link\_id, output, location='data/results'*)

Writes the results of a link execution to disk. If file encryption is enabled, the results file will contain ciphertext. :param link\_id: The link id of the result being written. :param output: The content of the link's output. :param location: The path to the results directory. :return:

## 14.5.9 app.service.learning\_svc module

**class** app.service.learning\_svc.**LearningService**

Bases: `app.service.interfaces.i_learning_svc.LearningServiceInterface`, `app.utility.base_service.BaseService`

**static add\_parsers** (*directory*)

**async build\_model** ()

The model is a static set of all variables used inside all ability commands This can be used to determine which facts - when found together - are more likely to be used together :return:

**async learn** (*facts, link, blob*)

## 14.5.10 app.service.planning\_svc module

**class** app.service.planning\_svc.**PlanningService**

Bases: `app.service.interfaces.i_planning_svc.PlanningServiceInterface`, `app.utility.base_planning_svc.BasePlanningService`

**async add\_ability\_to\_bucket** (*ability, bucket*)

Adds bucket tag to ability

**async check\_stopping\_conditions** (*stopping\_conditions, operation*)

Checks whether an operation has collected the proper facts to trigger this planner's stopping conditions

**Returns** True if all stopping conditions have been met, False if all stopping conditions have not been met

**async default\_next\_bucket** (*current\_bucket, state\_machine*)

Returns next bucket as specified in planner's defined bucket state machine. Loops from last bucket to first.

**async execute\_planner** (*planner*)

Default planner execution flow. Progress from bucket to bucket. Will stop execution for these conditions:

- All buckets have been executed.
- Planner stopping conditions have been met.
- Operation was halted from external/UI input.

NOTE: Do NOT call wait-for-link-completion functions here. Let the planner decide to do that within its bucket functions, and/or there are other planning\_svc utilities for the bucket functions to use to do so.

**async exhaust\_bucket** (*planner, bucket, operation, agent=None, batch=False, condition\_stop=True*)

Apply all links for specified bucket. Blocks until all links are completed, either after batch push, or separately for every pushed link.

### Parameters

- **planner** –
- **bucket** –
- **operation** –
- **agent** –
- **batch** – (bool) 'True' - push all bucket links immediately. Will check if operation has been stopped(by user) after all bucket links complete. 'False' will push links one at a time,

and wait for each to complete. Will check if operation has been stopped(by user) after each single link is completed.

- **condition\_stop** – (bool) check and respect stopping conditions

#### Returns

**async generate\_and\_trim\_links** (*agent, operation, abilities, trim=True*)

**async get\_cleanup\_links** (*operation, agent=None*)

For a given operation, create all cleanup links. If agent is supplied, only return cleanup links for that agent.  
:param operation: :param agent: :return: None

**async get\_links** (*operation, buckets=None, agent=None, trim=True, planner=None*)

For an operation and agent combination, create links (that can be executed). When no agent is supplied, links for all agents are returned

#### Parameters

- **operation** –
- **bucket** – ‘None’ - no buckets, get all links for given operation, agent, trim setting  
‘<bucket>’ - get links for specified bucket for given trim setting
- **agent** –
- **trim** – call trim\_links() on list of links before returning
- **planner** –

**Returns** a list of links

**async static sort\_links** (*links*)

Sort links by their score then by the order they are defined in an adversary profile

**async update\_stopping\_condition\_met** (*planner, operation*)

## 14.5.11 app.service.rest\_svc module

**class** app.service.rest\_svc.**RestService**

Bases: *app.service.interfaces.i\_rest\_svc.RestServiceInterface, app.utility.base\_service.BaseService*

**async apply\_potential\_link** (*link*)

**async construct\_agents\_for\_group** (*group*)

**async create\_operation** (*access, data*)

**async create\_schedule** (*access, data*)

**async delete\_ability** (*data*)

**async delete\_adversary** (*data*)

**async delete\_agent** (*data*)

**async delete\_operation** (*data*)

**async display\_objects** (*object\_name, data*)

**async display\_operation\_report** (*data*)

**async display\_result** (*data*)

**async download\_contact\_report** (*contact*)

```
async find_abilities (paw)
async get_link_pin (json_data)
async get_potential_links (op_id, paw=None)
async list_payloads ()
async persist_ability (data)
async persist_adversary (data)
    Save a new adversary from either the GUI or REST API. This writes a new YML file into the core data/
    directory. :param data: :return: the ID of the created adversary
async persist_source (data)
async task_agent_with_ability (paw, ability_id, facts=())
async update_agent_data (data)
async update_chain_data (data)
async update_config (data)
async update_operation (op_id, state=None, autonomous=None, obfuscator=None)
async update_planner (data)
    Update a new planner from either the GUI or REST API with new stopping conditions. This overwrites
    the existing YML file. :param data: :return: the ID of the created adversary
```

## 14.6 app.utility namespace

### 14.6.1 Submodules

### 14.6.2 app.utility.base\_obfuscator module

```
class app.utility.base_obfuscator.BaseObfuscator (agent)
    Bases: app.utility.base_world.BaseWorld
    run (link, **kwargs)
```

### 14.6.3 app.utility.base\_object module

```
class app.utility.base_object.BaseObject
    Bases: app.utility.base_world.BaseWorld
    property access
    static clean (d)
    property display
    display_schema = None
    static hash (s)
    classmethod load (dict_obj)
    load_schema = None
    match (criteria)
```

```

replace_app_props (encoded_string)
static retrieve (collection, unique)
schema = None
update (field, value)

```

#### 14.6.4 app.utility.base\_parser module

```

class app.utility.base_parser.BaseParser (parser_info)
    Bases: object

    static broadcastip (blob)

    static email (blob)
        Parse out email addresses :param blob: :return:

    static filename (blob)
        Parse out filenames :param blob: :return:

    static ip (blob)

    static line (blob)
        Split a blob by line :param blob: :return:

    static load_json (blob)

    static set_value (search, match, used_facts)
        Determine the value of a source/target for a Relationship :param search: a fact property to look for; either
        a source or target fact :param match: a parsing match :param used_facts: a list of facts that were used in a
        command :return: either None, the value of a matched used_fact, or the parsing match

```

#### 14.6.5 app.utility.base\_planning\_svc module

```

class app.utility.base_planning_svc.BasePlanningService
    Bases: app.utility.base_service.BaseService

    async add_test_variants (links, agent, facts=(), rules=())
        Create a list of all possible links for a given set of templates

        Parameters
            • links –
            • agent –
            • facts –
            • rules –

        Returns updated list of links

    async obfuscate_commands (agent, obfuscator, links)

    re_index = re.compile('( ?<=\\[filters\\(\\)\\.+?(?=\\)\\] ) ')
    re_limited = re.compile('#{.*\\[*\\] }')
    re_trait = re.compile('( ?<=\\{\\}\\.+?(?=\\[\\] ) ')
    re_variable = re.compile('#{(.*?) }', re.DOTALL)

```

**async static remove\_completed\_links** (*operation, agent, links*)

Remove any links that have already been completed by the operation for the agent

**Parameters**

- **operation** –
- **links** –
- **agent** –

**Returns** updated list of links

**async static remove\_links\_above\_visibility** (*links, operation*)

**async static remove\_links\_missing\_facts** (*links*)

Remove any links that did not have facts encoded into command

**Parameters** **links** –

**Returns** updated list of links

**async remove\_links\_missing\_requirements** (*links, operation*)

**async trim\_links** (*operation, links, agent*)

**Trim links in supplied list. Where ‘trim’ entails:**

- adding all possible test variants
- removing completed links (i.e. agent has already completed)
- removing links that did not have template fact variables replaced by fact values

**Parameters**

- **operation** –
- **links** –
- **agent** –

**Returns** trimmed list of links

## 14.6.6 app.utility.base\_service module

**class** app.utility.base\_service.**BaseService**

Bases: *app.utility.base\_world.BaseWorld*

**add\_service** (*name, svc*)

**classmethod** **get\_service** (*name*)

**classmethod** **get\_services** ()

## 14.6.7 app.utility.base\_world module

```
class app.utility.base_world.AccessSchema (*, only: Union[Sequence[str], Set[str]] = None,
exclude: Union[Sequence[str], Set[str]] = (),
many: bool = False, context: Dict = None,
load_only: Union[Sequence[str], Set[str]] = (),
dump_only: Union[Sequence[str], Set[str]] =
(), partial: Union[bool, Sequence[str], Set[str]]
= False, unknown: str = None)
```

Bases: `marshmallow.schema.Schema`

`opts = <marshmallow.schema.SchemaOpts object>`

```
class app.utility.base_world.BaseWorld
```

Bases: `object`

A collection of base static functions for service & object module usage

```
class Access
```

Bases: `enum.Enum`

An enumeration.

`APP = 0`

`BLUE = 2`

`RED = 1`

```
class Privileges
```

Bases: `enum.Enum`

An enumeration.

`Elevated = 1`

`User = 0`

```
static apply_config (name, config)
```

```
static check_requirement (params)
```

```
static create_logger (name)
```

```
static decode_bytes (s)
```

```
static encode_string (s)
```

```
static generate_name (size=16)
```

```
static generate_number (size=6)
```

```
static get_config (prop=None, name=None)
```

```
static get_current_timestamp (date_format='%Y-%m-%d %H:%M:%S')
```

```
static get_version (path='.')
```

```
static is_base64 (s)
```

```
static is_uuid4 (s)
```

```
static jitter (fraction)
```

```
async static load_module (module_type, module_info)
```

```
static prepend_to_file (filename, line)
```

```

re_base64 = re.compile('[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}',
static set_config(name, prop, value)
static strip_yaml(path)
async static walk_file_path(path, target)
class app.utility.base_world.PrivilegesSchema(*, only: Union[Sequence[str], Set[str]]
= None, exclude: Union[Sequence[str],
Set[str]] = (), many: bool = False,
context: Dict = None, load_only:
Union[Sequence[str], Set[str]] = (),
dump_only: Union[Sequence[str],
Set[str]] = (), partial: Union[bool, Se-
quence[str], Set[str]] = False, unknown:
str = None)
Bases: marshmallow.schema.Schema
opts = <marshmallow.schema.SchemaOpts object>

```

### 14.6.8 app.utility.config\_generator module

```

app.utility.config_generator.ensure_local_config()
    Checks if a local.yml config file exists. If not, generates a new local.yml file using secure random values.
app.utility.config_generator.log_config_message(config_path)
app.utility.config_generator.make_secure_config()

```

### 14.6.9 app.utility.file\_decryptor module

```

app.utility.file_decryptor.decrypt(filename, configuration, output_file=None,
b64decode=False)
app.utility.file_decryptor.get_encryptor(salt, key)
app.utility.file_decryptor.read(filename, encryptor)

```

### 14.6.10 app.utility.payload\_encoder module

This module contains helper functions for encoding and decoding payload files.

If AV is running on the server host, then it may sometimes flag, quarantine, or delete CALDERA payloads. To help prevent this, encoded payloads can be used to prevent AV from breaking the server. The convention expected by the server is that encoded payloads will be XOR'ed with the DEFAULT\_KEY contained in the payload\_encoder.py module.

Additionally, payload\_encoder.py can be used from the command-line to add a new encoded payload.

```
python /path/to/payload_encoder.py input_file output_file`
```

NOTE: In order for the server to detect the availability of an encoded payload, the payload file's name must end in the `.xored` extension.

```

app.utility.payload_encoder.xor_bytes(in_bytes, key=None)
app.utility.payload_encoder.xor_file(input_file, output_file=None, key=None)

```



---

### 14.6.11 app.utility.rule\_set module

**class** app.utility.rule\_set.**RuleAction**

Bases: enum.Enum

An enumeration.

**ALLOW = 1**

**DENY = 0**

**class** app.utility.rule\_set.**RuleSet** (*rules*)

Bases: object

**async apply\_rules** (*facts*)

**async is\_fact\_allowed** (*fact*)



## INDICES AND TABLES

- genindex
- modindex
- search



## PYTHON MODULE INDEX

### a

- app.api.packs.advanced, 41
- app.api.packs.campaign, 41
- app.api.rest\_api, 41
- app.contacts.contact\_gist, 42
- app.contacts.contact\_html, 43
- app.contacts.contact\_http, 43
- app.contacts.contact\_tcp, 43
- app.contacts.contact\_udp, 43
- app.contacts.contact\_websocket, 43
- app.contacts.handles.h\_beacon, 42
- app.learning.p\_ip, 44
- app.learning.p\_path, 44
- app.objects.c\_ability, 52
- app.objects.c\_adversary, 53
- app.objects.c\_agent, 54
- app.objects.c\_obfuscator, 55
- app.objects.c\_operation, 55
- app.objects.c\_planner, 57
- app.objects.c\_plugin, 57
- app.objects.c\_schedule, 58
- app.objects.c\_source, 58
- app.objects.interfaces.i\_object, 44
- app.objects.secondclass.c\_fact, 44
- app.objects.secondclass.c\_instruction, 45
- app.objects.secondclass.c\_link, 46
- app.objects.secondclass.c\_parser, 46
- app.objects.secondclass.c\_parserconfig, 47
- app.objects.secondclass.c\_relationship, 48
- app.objects.secondclass.c\_requirement, 49
- app.objects.secondclass.c\_result, 49
- app.objects.secondclass.c\_rule, 50
- app.objects.secondclass.c\_variation, 50
- app.objects.secondclass.c\_visibility, 51
- app.service.app\_svc, 64
- app.service.auth\_svc, 64
- app.service.contact\_svc, 65
- app.service.data\_svc, 66
- app.service.event\_svc, 66
- app.service.file\_svc, 67
- app.service.interfaces.i\_app\_svc, 59
- app.service.interfaces.i\_auth\_svc, 60
- app.service.interfaces.i\_contact\_svc, 60
- app.service.interfaces.i\_data\_svc, 60
- app.service.interfaces.i\_event\_svc, 61
- app.service.interfaces.i\_file\_svc, 61
- app.service.interfaces.i\_learning\_svc, 62
- app.service.interfaces.i\_planning\_svc, 62
- app.service.interfaces.i\_rest\_svc, 63
- app.service.learning\_svc, 68
- app.service.planning\_svc, 68
- app.service.rest\_svc, 69
- app.utility.base\_obfuscator, 70
- app.utility.base\_object, 70
- app.utility.base\_parser, 71
- app.utility.base\_planning\_svc, 71
- app.utility.base\_service, 72
- app.utility.base\_world, 73
- app.utility.config\_generator, 74
- app.utility.file\_decryptor, 74
- app.utility.payload\_encoder, 74
- app.utility.rule\_set, 75



## A

- Ability (class in *app.objects.c\_ability*), 52
- ability\_id() (*app.objects.c\_source.Adjustment property*), 58
- AbilitySchema (class in *app.objects.c\_ability*), 52
- accept() (*app.contacts.contact\_tcp.TcpSessionHandler method*), 43
- access() (*app.utility.base\_object.BaseObject property*), 70
- AccessSchema (class in *app.utility.base\_world*), 73
- active\_agents() (*app.objects.c\_operation.Operation method*), 55
- add\_ability\_to\_bucket() (*app.service.planning\_svc.PlanningService method*), 68
- add\_bucket() (*app.objects.c\_ability.Ability method*), 52
- add\_link() (*app.objects.c\_operation.Operation method*), 56
- add\_parsers() (*app.service.interfaces.i\_learning\_svc.LearningServiceInterface static method*), 62
- add\_parsers() (*app.service.learning\_svc.LearningService static method*), 68
- add\_service() (*app.utility.base\_service.BaseService method*), 72
- add\_special\_payload() (*app.service.file\_svc.FileSvc method*), 67
- add\_special\_payload() (*app.service.interfaces.i\_file\_svc.FileServiceInterface method*), 61
- add\_test\_variants() (*app.utility.base\_planning\_svc.BasePlanningService method*), 71
- Adjustment (class in *app.objects.c\_source*), 58
- AdjustmentSchema (class in *app.objects.c\_source*), 58
- AdvancedPack (class in *app.api.packs.advanced*), 41
- Adversary (class in *app.objects.c\_adversary*), 53
- AdversarySchema (class in *app.objects.c\_adversary*), 53
- Agent (class in *app.objects.c\_agent*), 54
- AgentFieldsSchema (class in *app.objects.c\_agent*), 54
- AgentSchema (class in *app.objects.c\_agent*), 54
- all\_facts() (*app.objects.c\_agent.Agent method*), 54
- all\_facts() (*app.objects.c\_operation.Operation method*), 56
- all\_relationships() (*app.objects.c\_operation.Operation method*), 56
- ALLOW (*app.utility.rule\_set.RuleAction attribute*), 75
- api\_access() (in module *app.contacts.contact\_gist*), 42
- APP (*app.utility.base\_world.BaseWorld.Access attribute*), 73
- app.api.packs.advanced (module), 41
- app.api.packs.campaign (module), 41
- app.api.rest\_api (module), 41
- app.contacts.contact\_gist (module), 42
- app.contacts.contact\_html (module), 43
- app.contacts.contact\_http (module), 43
- app.contacts.contact\_tcp (module), 43
- app.contacts.contact\_udp (module), 43
- app.contacts.contact\_websocket (module), 43
- app.contacts.handles.h\_beacon (module), 42
- app.learning.p\_ip (module), 44
- app.learning.p\_path (module), 44
- app.objects.c\_ability (module), 52
- app.objects.c\_adversary (module), 53
- app.objects.c\_agent (module), 54
- app.objects.c\_obfuscator (module), 55
- app.objects.c\_operation (module), 55
- app.objects.c\_planner (module), 57
- app.objects.c\_plugin (module), 57
- app.objects.c\_schedule (module), 58
- app.objects.c\_source (module), 58
- app.objects.interfaces.i\_object (module), 44
- app.objects.secondclass.c\_fact (module), 44
- app.objects.secondclass.c\_instruction (module), 45
- app.objects.secondclass.c\_link (module), 45

- 46
- `app.objects.secondclass.c_parser` (module), 46
- `app.objects.secondclass.c_parserconfig` (module), 47
- `app.objects.secondclass.c_relationship` (module), 48
- `app.objects.secondclass.c_requirement` (module), 49
- `app.objects.secondclass.c_result` (module), 49
- `app.objects.secondclass.c_rule` (module), 50
- `app.objects.secondclass.c_variation` (module), 50
- `app.objects.secondclass.c_visibility` (module), 51
- `app.service.app_svc` (module), 64
- `app.service.auth_svc` (module), 64
- `app.service.contact_svc` (module), 65
- `app.service.data_svc` (module), 66
- `app.service.event_svc` (module), 66
- `app.service.file_svc` (module), 67
- `app.service.interfaces.i_app_svc` (module), 59
- `app.service.interfaces.i_auth_svc` (module), 60
- `app.service.interfaces.i_contact_svc` (module), 60
- `app.service.interfaces.i_data_svc` (module), 60
- `app.service.interfaces.i_event_svc` (module), 61
- `app.service.interfaces.i_file_svc` (module), 61
- `app.service.interfaces.i_learning_svc` (module), 62
- `app.service.interfaces.i_planning_svc` (module), 62
- `app.service.interfaces.i_rest_svc` (module), 63
- `app.service.learning_svc` (module), 68
- `app.service.planning_svc` (module), 68
- `app.service.rest_svc` (module), 69
- `app.utility.base_obfuscator` (module), 70
- `app.utility.base_object` (module), 70
- `app.utility.base_parser` (module), 71
- `app.utility.base_planning_svc` (module), 71
- `app.utility.base_service` (module), 72
- `app.utility.base_world` (module), 73
- `app.utility.config_generator` (module), 74
- `app.utility.file_decryptor` (module), 74
- `app.utility.payload_encoder` (module), 74
- `app.utility.rule_set` (module), 75
- `apply()` (`app.objects.c_operation.Operation` method), 56
- `apply()` (`app.objects.secondclass.c_visibility.Visibility` method), 51
- `apply()` (`app.service.auth_svc.AuthService` method), 65
- `apply()` (`app.service.data_svc.DataService` method), 66
- `apply()` (`app.service.interfaces.i_auth_svc.AuthServiceInterface` method), 60
- `apply()` (`app.service.interfaces.i_data_svc.DataServiceInterface` method), 60
- `apply_config()` (`app.utility.base_world.BaseWorld` static method), 73
- `apply_id()` (`app.objects.secondclass.c_link.Link` method), 46
- `apply_potential_link()` (`app.service.interfaces.i_rest_svc.RestServiceInterface` method), 63
- `apply_potential_link()` (`app.service.rest_svc.RestService` method), 69
- `apply_rules()` (`app.utility.rule_set.RuleSet` method), 75
- `AppService` (class in `app.service.app_svc`), 64
- `AppServiceInterface` (class in `app.service.interfaces.i_app_svc`), 59
- `authorized_userid()` (`app.service.auth_svc.DictionaryAuthorizationPolicy` method), 65
- `AuthService` (class in `app.service.auth_svc`), 64
- `AuthService.User` (class in `app.service.auth_svc`), 64
- `AuthServiceInterface` (class in `app.service.interfaces.i_auth_svc`), 60
- ## B
- `BaseObfuscator` (class in `app.utility.base_obfuscator`), 70
- `BaseObject` (class in `app.utility.base_object`), 70
- `BaseParser` (class in `app.utility.base_parser`), 71
- `BasePlanningService` (class in `app.utility.base_planning_svc`), 71
- `BaseService` (class in `app.utility.base_service`), 72
- `BaseWorld` (class in `app.utility.base_world`), 73
- `BaseWorld.Access` (class in `app.utility.base_world`), 73
- `BaseWorld.Privileges` (class in `app.utility.base_world`), 73
- `BLUE` (`app.utility.base_world.BaseWorld.Access` attribute), 73
- `bootstrap()` (`app.objects.c_agent.Agent` method), 54
- `broadcastip()` (`app.utility.base_parser.BaseParser` static method), 71



build\_ability() (*app.objects.c\_ability.AbilitySchema* **C**  
     *method*), 53  
 build\_adjustment() (*app.objects.c\_source.AdjustmentSchema*  
     *method*), 58  
 build\_adversary() (*app.objects.c\_adversary.AdversarySchema*  
     *method*), 53  
 build\_agent() (*app.objects.c\_agent.AgentSchema*  
     *method*), 54  
 build\_fact() (*app.objects.secondclass.c\_fact.FactSchema*  
     *method*), 45  
 build\_filename() (*app.service.contact\_svc.ContactService*  
     *method*), 65  
 build\_filename() (*app.service.interfaces.i\_contact\_svc.ContactServiceInterface*  
     *method*), 60  
 build\_instruction() (*app.objects.secondclass.c\_instruction.InstructionSchema*  
     *method*), 45  
 build\_link() (*app.objects.secondclass.c\_link.LinkSchema*  
     *method*), 46  
 build\_model() (*app.service.interfaces.i\_learning\_svc.LearningServiceInterface*  
     *method*), 62  
 build\_model() (*app.service.learning\_svc.LearningService*  
     *method*), 68  
 build\_parser() (*app.objects.secondclass.c\_parser.ParserSchema*  
     *method*), 47  
 build\_parserconfig() (*app.objects.secondclass.c\_parserconfig.ParserConfigSchema*  
     *method*), 47  
 build\_planner() (*app.objects.c\_operation.OperationSchema*  
     *method*), 56  
 build\_planner() (*app.objects.c\_planner.PlannerSchema*  
     *method*), 57  
 build\_plugin() (*app.objects.c\_plugin.PluginSchema*  
     *method*), 57  
 build\_relationship() (*app.objects.secondclass.c\_relationship.RelationshipSchema*  
     *method*), 48  
 build\_requirement() (*app.objects.secondclass.c\_requirement.RequirementSchema*  
     *method*), 49  
 build\_result() (*app.objects.secondclass.c\_result.ResultSchema*  
     *method*), 49  
 build\_rule() (*app.objects.secondclass.c\_rule.RuleSchema*  
     *method*), 50  
 build\_source() (*app.objects.c\_source.SourceSchema*  
     *method*), 59  
 build\_variation() (*app.objects.secondclass.c\_variation.VariationSchema*  
     *method*), 51  
 build\_visibility() (*app.objects.secondclass.c\_visibility.VisibilitySchema*  
     *method*), 52  
 calculate\_sleep() (*app.objects.c\_agent.Agent*  
     *method*), 54  
 CampaignPack (*class in app.api.packs.campaign*), 41  
 can\_ignore() (*app.objects.secondclass.c\_link.Link*  
     *method*), 46  
 capabilities() (*app.objects.c\_agent.Agent*  
     *method*), 54  
 check\_authorization() (*in module*  
     *app.service.auth\_svc*), 65  
 check\_edge\_target() (*app.objects.secondclass.c\_parserconfig.ParserConfigSchema*  
     *method*), 48  
 check\_permissions() (*app.service.auth\_svc.AuthService* *method*), 65  
 check\_permissions() (*app.service.interfaces.i\_auth\_svc.AuthServiceInterface*  
     *method*), 60  
 check\_requirement() (*app.utility.base\_world.BaseWorld* *static*  
     *method*), 73  
 check\_stopping\_conditions() (*app.service.planning\_svc.PlanningService*  
     *method*), 68  
 clean() (*app.utility.base\_object.BaseObject* *static*  
     *method*), 70  
 close() (*app.objects.c\_operation.Operation* *method*),  
     56  
 command() (*app.objects.secondclass.c\_variation.Variation*  
     *property*), 50  
 compile\_go() (*app.service.file\_svc.FileSvc* *method*),  
     67  
 compile\_go() (*app.service.interfaces.i\_file\_svc.FileServiceInterface*  
     *method*), 61  
 construct\_agents\_for\_group() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface*  
     *method*), 63  
 construct\_agents\_for\_group() (*app.service.rest\_svc.RestService* *method*),  
     69  
 ContactService (*class in app.service.contact\_svc*),  
     65  
 ContactServiceInterface (*class in*  
     *app.service.interfaces.i\_contact\_svc*), 60  
 create\_exfil\_sub\_directory() (*app.service.file\_svc.FileSvc* *method*), 67  
 create\_exfil\_sub\_directory() (*app.service.interfaces.i\_file\_svc.FileServiceInterface*  
     *method*), 61  
 create\_logger() (*app.utility.base\_world.BaseWorld*  
     *static method*), 73  
 create\_operation() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface*  
     *method*), 63

create\_operation() (app.service.rest\_svc.RestService method), 69  
 create\_schedule() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 create\_schedule() (app.service.rest\_svc.RestService method), 69  
**D**  
 datagram\_received() (app.contacts.contact\_udp.Handler method), 43  
 DataService (class in app.service.data\_svc), 66  
 DataServiceInterface (class in app.service.interfaces.i\_data\_svc), 60  
 decode\_bytes() (app.utility.base\_world.BaseWorld static method), 73  
 decrypt() (in module app.utility.file\_decryptor), 74  
 default\_next\_bucket() (app.service.planning\_svc.PlanningService method), 68  
 delete\_ability() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 delete\_ability() (app.service.rest\_svc.RestService method), 69  
 delete\_adversary() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 delete\_adversary() (app.service.rest\_svc.RestService method), 69  
 delete\_agent() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 delete\_agent() (app.service.rest\_svc.RestService method), 69  
 delete\_operation() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 delete\_operation() (app.service.rest\_svc.RestService method), 69  
 DENY (app.utility.rule\_set.RuleAction attribute), 75  
 destroy() (app.objects.c\_plugin.Plugin method), 57  
 destroy() (app.service.data\_svc.DataService static method), 66  
 destroy() (app.service.interfaces.i\_data\_svc.DataServiceInterface static method), 60  
 DictionaryAuthorizationPolicy (class in app.service.auth\_svc), 65  
 display() (app.objects.secondclass.c\_instruction.Instruction property), 45  
 display() (app.objects.secondclass.c\_relationship.Relationship property), 48  
 display() (app.objects.secondclass.c\_visibility.Visibility property), 51  
 display() (app.utility.base\_object.BaseObject property), 70  
 display\_name() (app.objects.c\_agent.Agent property), 54  
 display\_objects() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 display\_objects() (app.service.rest\_svc.RestService method), 69  
 display\_operation\_report() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 display\_operation\_report() (app.service.rest\_svc.RestService method), 69  
 display\_result() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 display\_result() (app.service.rest\_svc.RestService method), 69  
 display\_schema (app.objects.c\_ability.Ability attribute), 52  
 display\_schema (app.objects.c\_obfuscator.Obfuscator attribute), 55  
 display\_schema (app.objects.c\_planner.Planner attribute), 57  
 display\_schema (app.objects.c\_plugin.Plugin attribute), 57  
 display\_schema (app.objects.c\_source.Source attribute), 59  
 display\_schema (app.objects.secondclass.c\_link.Link attribute), 46  
 display\_schema (app.utility.base\_object.BaseObject attribute), 70  
 download\_contact\_report() (app.service.interfaces.i\_rest\_svc.RestServiceInterface method), 63  
 download\_contact\_report() (app.service.rest\_svc.RestService method), 69  
 download\_file() (app.api.rest\_api.RestApi method), 41  
**E**  
 Elevated (app.utility.base\_world.BaseWorld.Privileges attribute), 73  
 email() (app.utility.base\_parser.BaseParser static method), 71  
 enable() (app.api.packs.advanced.AdvancedPack method), 41

enable() (*app.api.packs.campaign.CampaignPack method*), 41  
 enable() (*app.api.rest\_api.RestApi method*), 41  
 enable() (*app.objects.c\_plugin.Plugin method*), 57  
 encode\_string() (*app.utility.base\_world.BaseWorld static method*), 73  
 ensure\_local\_config() (*in module app.utility.config\_generator*), 74  
 Error (*class in app.service.app\_svc*), 64  
 errors() (*app.service.app\_svc.AppService property*), 64  
 escaped() (*app.objects.secondclass.c\_fact.Fact method*), 44  
 EventService (*class in app.service.event\_svc*), 66  
 EventServiceInterface (*class in app.service.interfaces.i\_event\_svc*), 61  
 execute\_planner() (*app.service.planning\_svc.PlanningService method*), 68  
 EXECUTOR (*app.objects.c\_operation.Operation.Reason attribute*), 55  
 exhaust\_bucket() (*app.service.planning\_svc.PlanningService method*), 68  
 expand() (*app.objects.c\_plugin.Plugin method*), 57

## F

Fact (*class in app.objects.secondclass.c\_fact*), 44  
 FACT\_DEPENDENCY (*app.objects.c\_operation.Operation.Reason attribute*), 55  
 FactSchema (*class in app.objects.secondclass.c\_fact*), 44  
 filename() (*app.utility.base\_parser.BaseParser static method*), 71  
 FileServiceInterface (*class in app.service.interfaces.i\_file\_svc*), 61  
 FileSvc (*class in app.service.file\_svc*), 67  
 find\_abilities() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface method*), 63  
 find\_abilities() (*app.service.rest\_svc.RestService method*), 69  
 find\_file\_path() (*app.service.file\_svc.FileSvc method*), 67  
 find\_file\_path() (*app.service.interfaces.i\_file\_svc.FileServiceInterface method*), 61  
 find\_link() (*app.service.app\_svc.AppService method*), 64  
 find\_link() (*app.service.interfaces.i\_app\_svc.AppServiceInterface method*), 59  
 find\_op\_with\_link() (*app.service.app\_svc.AppService method*), 64  
 find\_op\_with\_link() (*app.service.interfaces.i\_app\_svc.AppServiceInterface method*), 59

fire\_event() (*app.service.event\_svc.EventService method*), 66  
 fire\_event() (*app.service.interfaces.i\_event\_svc.EventServiceInterface method*), 61  
 FirstClassObjectInterface (*class in app.objects.interfaces.i\_object*), 44  
 fix\_adjustments() (*app.objects.c\_source.SourceSchema method*), 59  
 fix\_id() (*app.objects.c\_adversary.AdversarySchema method*), 53  
 fix\_relationships() (*app.objects.secondclass.c\_parser.ParserSchema method*), 47  
 for\_all\_public\_methods() (*in module app.service.auth\_svc*), 65  
 from\_json() (*app.objects.secondclass.c\_relationship.Relationship class method*), 48

## G

generate\_and\_trim\_links() (*app.service.interfaces.i\_planning\_svc.PlanningServiceInterface method*), 62  
 generate\_and\_trim\_links() (*app.service.planning\_svc.PlanningService method*), 69  
 generate\_name() (*app.utility.base\_world.BaseWorld static method*), 73  
 generate\_number() (*app.utility.base\_world.BaseWorld static method*), 73  
 get\_active\_agent\_by\_paw() (*app.objects.c\_operation.Operation method*), 56  
 get\_beacons() (*app.contacts.contact\_gist.Gist method*), 42  
 get\_cleanup\_links() (*app.service.interfaces.i\_planning\_svc.PlanningServiceInterface method*), 62  
 get\_cleanup\_links() (*app.service.planning\_svc.PlanningService method*), 69  
 get\_contact() (*app.service.interfaces.i\_app\_svc.AppServiceInterface method*), 59  
 get\_contact() (*app.service.contact\_svc.ContactService method*), 65  
 get\_contact\_timestamp() (*app.utility.base\_world.BaseWorld static method*), 73  
 get\_encryptor() (*in module app.utility.file\_decryptor*), 74  
 get\_file() (*app.service.file\_svc.FileSvc method*), 67  
 get\_file() (*app.service.interfaces.i\_file\_svc.FileServiceInterface method*), 61

get\_link\_pin() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface* (class in *app.contacts.contact\_udp*), 43  
     method), 63  
 get\_link\_pin() (*app.service.rest\_svc.RestService* (class in *app.contacts.contact\_websocket*), 43  
     method), 70  
 get\_links() (*app.service.interfaces.i\_planning\_svc.PlanningServiceInterface* (class in *app.objects.c\_operation.Operation*  
     method), 62  
     method), 56  
 get\_links() (*app.service.planning\_svc.PlanningService* (class in *app.objects.c\_operation.Operation*  
     method), 69  
     method), 56  
 get\_payload\_name\_from\_uuid() (*app.service.file\_svc.FileSvc* (class in *app.utility.base\_object.BaseObject* static  
     method), 67  
     method), 70  
 get\_payload\_name\_from\_uuid() (*app.service.interfaces.i\_file\_svc.FileServiceInterface* (class in *app.objects.c\_agent.Agent* method), 54  
     method), 61  
 get\_permissions() (*app.service.auth\_svc.AuthService* (class in *app.objects.c\_ability.Ability* attribute), 52  
     method), 65  
 get\_permissions() (*app.service.interfaces.i\_auth\_svc.AuthServiceInterface* (class in *app.contacts.contact\_html*), 43  
     method), 60  
     method), 43  
 get\_potential\_links() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface* (class in *app.contacts.contact\_http*), 43  
     method), 63  
     method), 45  
 get\_potential\_links() (*app.service.rest\_svc.RestService* (class in *app.objects.secondclass.c\_instruction*), 45  
     method), 70  
     method), 45  
 get\_results() (*app.contacts.contact\_gist.Gist* (class in *app.utility.base\_parser.BaseParser* static method),  
     method), 42  
     method), 71  
 get\_service() (*app.utility.base\_service.BaseService* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     class method), 72  
 get\_services() (*app.utility.base\_service.BaseService* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     class method), 72  
 get\_version() (*app.utility.base\_world.BaseWorld* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     static method), 73  
 Gist (class in *app.contacts.contact\_gist*), 42  
 gist\_operation\_loop() (*app.contacts.contact\_gist.Gist* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 42  
 gui\_modification() (*app.objects.c\_agent.Agent* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 54

## H

Handle (class in *app.contacts.handles.h\_beacon*), 42  
 handle() (*app.contacts.contact\_websocket.Handler* (class in *app.contacts.contact\_gist.Gist* method), 42  
     method), 43  
 handle\_beacons() (*app.contacts.contact\_gist.Gist* (class in *app.service.event\_svc.EventService* method), 66  
     method), 42  
 handle\_exceptions() (*app.service.event\_svc.EventService* (class in *app.service.contact\_svc.ContactService*  
     method), 65  
     method), 66  
 handle\_heartbeat() (*app.service.contact\_svc.ContactService* (class in *app.service.interfaces.i\_contact\_svc.ContactServiceInterface*  
     method), 60  
     method), 65  
 handle\_heartbeat() (*app.service.interfaces.i\_contact\_svc.ContactServiceInterface* (class in *app.utility.base\_parser.BaseParser* static  
     method), 71  
     method), 60

Handler (class in *app.contacts.contact\_websocket*), 43  
 has\_ability() (*app.objects.c\_adversary.Adversary* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 53  
 has\_link() (*app.objects.c\_operation.Operation* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 56  
 hash() (*app.utility.base\_object.BaseObject* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     static method), 70  
 heartbeat\_modification() (*app.objects.c\_agent.Agent* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 54  
 HOOKS (*app.objects.c\_ability.Ability* attribute), 52  
 Html (class in *app.contacts.contact\_html*), 43  
 Http (class in *app.contacts.contact\_http*), 43  
 Instruction (class in *app.objects.secondclass.c\_instruction*), 45  
 InstructionSchema (class in *app.objects.secondclass.c\_instruction*), 45  
 ip() (*app.utility.base\_parser.BaseParser* static method), 71  
 is\_base64() (*app.utility.base\_world.BaseWorld* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     static method), 73  
 is\_closeable() (*app.objects.c\_operation.Operation* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 56  
 is\_fact\_allowed() (*app.utility.rule\_set.RuleSet* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 75  
 is\_finished() (*app.objects.c\_operation.Operation* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 56  
 is\_uuid4() (*app.utility.base\_world.BaseWorld* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     static method), 73

## J

jitter() (*app.utility.base\_world.BaseWorld* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     static method), 73

## K

kill() (*app.objects.c\_agent.Agent* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     method), 54

## L

landing() (*app.api.rest\_api.RestApi* (class in *app.service.interfaces.i\_learning\_svc.LearningServiceInterface*  
     method), 62  
     method), 41  
 learn() (*app.service.interfaces.i\_learning\_svc.LearningServiceInterface* (class in *app.service.learning\_svc.LearningService*  
     method), 68  
     method), 62  
 learn() (*app.service.learning\_svc.LearningService* (class in *app.service.interfaces.i\_learning\_svc*), 62  
     method), 68  
 LearningService (class in *app.service.interfaces.i\_learning\_svc*), 62  
 LearningServiceInterface (class in *app.utility.base\_parser.BaseParser* static method), 71  
     method), 62  
 line() (*app.utility.base\_parser.BaseParser* (class in *app.utility.base\_world.BaseWorld* static method), 73  
     static method), 71

- Link (class in *app.objects.secondclass.c\_link*), 46
- link\_status() (*app.objects.c\_operation.Operation* method), 56
- LinkSchema (class in *app.objects.secondclass.c\_link*), 46
- LinkSchema.Meta (class in *app.objects.secondclass.c\_link*), 46
- list\_payloads() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface* method), 63
- list\_payloads() (*app.service.rest\_svc.RestService* method), 70
- load() (*app.objects.c\_obfuscator.Obfuscator* method), 55
- load() (*app.utility.base\_object.BaseObject* class method), 70
- load\_data() (*app.service.data\_svc.DataService* method), 66
- load\_data() (*app.service.interfaces.i\_data\_svc.DataServiceInterface* method), 60
- load\_json() (*app.utility.base\_parser.BaseParser* static method), 71
- load\_module() (*app.utility.base\_world.BaseWorld* static method), 73
- load\_plugin() (*app.objects.c\_plugin.Plugin* method), 57
- load\_plugin\_expansions() (*app.service.app\_svc.AppService* method), 64
- load\_plugin\_expansions() (*app.service.interfaces.i\_app\_svc.AppServiceInterface* method), 59
- load\_plugins() (*app.service.app\_svc.AppService* method), 64
- load\_plugins() (*app.service.interfaces.i\_app\_svc.AppServiceInterface* method), 59
- load\_schema (*app.objects.c\_agent.Agent* attribute), 54
- load\_schema (*app.objects.secondclass.c\_fact.Fact* attribute), 44
- load\_schema (*app.objects.secondclass.c\_link.Link* attribute), 46
- load\_schema (*app.objects.secondclass.c\_relationship.Relationship* attribute), 48
- load\_schema (*app.utility.base\_object.BaseObject* attribute), 70
- locate() (*app.service.data\_svc.DataService* method), 66
- locate() (*app.service.interfaces.i\_data\_svc.DataServiceInterface* method), 60
- log\_config\_message() (in module *app.utility.config\_generator*), 74
- login() (*app.api.rest\_api.RestApi* method), 41
- login\_user() (*app.service.auth\_svc.AuthService* method), 65
- login\_user() (*app.service.interfaces.i\_auth\_svc.AuthServiceInterface* method), 60
- logout() (*app.api.rest\_api.RestApi* method), 41
- logout\_user() (*app.service.auth\_svc.AuthService* static method), 65
- logout\_user() (*app.service.interfaces.i\_auth\_svc.AuthServiceInterface* static method), 60
- ## M
- make\_secure\_config() (in module *app.utility.config\_generator*), 74
- match() (*app.utility.base\_object.BaseObject* method), 70
- MAX\_SCORE (*app.objects.secondclass.c\_visibility.Visibility* attribute), 51
- MIN\_SCORE (*app.objects.secondclass.c\_visibility.Visibility* attribute), 51
- msg\_type (*app.service.app\_svc.Error* property), 64
- ## N
- name() (*app.service.app\_svc.Error* property), 64
- ## O
- obfuscate\_commands() (*app.utility.base\_planning\_svc.BasePlanningService* method), 71
- Obfuscator (class in *app.objects.c\_obfuscator*), 55
- ObfuscatorSchema (class in *app.objects.c\_obfuscator*), 55
- observe\_event() (*app.service.event\_svc.EventService* method), 66
- observe\_event() (*app.service.interfaces.i\_event\_svc.EventServiceInterface* method), 61
- offset() (*app.objects.c\_source.Adjustment* property), 58
- OP\_RUNNING (*app.objects.c\_operation.Operation.Reason* attribute), 55
- Operation (class in *app.objects.c\_operation*), 55
- Operation.Reason (class in *app.objects.c\_operation*), 55
- operation\_loop() (*app.contacts.contact\_tcp.Tcp* method), 43
- OperationSchema (class in *app.objects.c\_operation*), 56
- opts (*app.objects.c\_ability.AbilitySchema* attribute), 53
- opts (*app.objects.c\_adversary.AdversarySchema* attribute), 53
- opts (*app.objects.c\_agent.AgentFieldsSchema* attribute), 54
- opts (*app.objects.c\_agent.AgentSchema* attribute), 55
- opts (*app.objects.c\_obfuscator.ObfuscatorSchema* attribute), 55
- opts (*app.objects.c\_operation.OperationSchema* attribute), 56

- opts (*app.objects.c\_planner.PlannerSchema* attribute), 57
- opts (*app.objects.c\_plugin.PluginSchema* attribute), 58
- opts (*app.objects.c\_schedule.ScheduleSchema* attribute), 58
- opts (*app.objects.c\_source.AdjustmentSchema* attribute), 58
- opts (*app.objects.c\_source.SourceSchema* attribute), 59
- opts (*app.objects.secondclass.c\_fact.FactSchema* attribute), 45
- opts (*app.objects.secondclass.c\_instruction.InstructionSchema* attribute), 45
- opts (*app.objects.secondclass.c\_link.LinkSchema* attribute), 46
- opts (*app.objects.secondclass.c\_parser.ParserSchema* attribute), 47
- opts (*app.objects.secondclass.c\_parserconfig.ParserConfigSchema* attribute), 48
- opts (*app.objects.secondclass.c\_relationship.RelationshipSchema* attribute), 48
- opts (*app.objects.secondclass.c\_requirement.RequirementSchema* attribute), 49
- opts (*app.objects.secondclass.c\_result.ResultSchema* attribute), 50
- opts (*app.objects.secondclass.c\_rule.RuleSchema* attribute), 50
- opts (*app.objects.secondclass.c\_variation.VariationSchema* attribute), 51
- opts (*app.objects.secondclass.c\_visibility.VisibilitySchema* attribute), 52
- opts (*app.utility.base\_world.AccessSchema* attribute), 73
- opts (*app.utility.base\_world.PrivilegesSchema* attribute), 74
- P**
- parse() (*app.learning.p\_ip.Parser* method), 44
- parse() (*app.learning.p\_path.Parser* method), 44
- parse() (*app.objects.secondclass.c\_link.Link* method), 46
- Parser (class in *app.learning.p\_ip*), 44
- Parser (class in *app.learning.p\_path*), 44
- Parser (class in *app.objects.secondclass.c\_parser*), 46
- ParserConfig (class in *app.objects.secondclass.c\_parserconfig*), 47
- ParserConfigSchema (class in *app.objects.secondclass.c\_parserconfig*), 47
- ParserConfigSchema.Meta (class in *app.objects.secondclass.c\_parserconfig*), 47
- ParserSchema (class in *app.objects.secondclass.c\_parser*), 46
- password() (*app.service.auth\_svc.AuthService.User* property), 64
- permissions() (*app.service.auth\_svc.AuthService.User* property), 64
- permits() (*app.service.auth\_svc.DictionaryAuthorizationPolicy* method), 65
- persist\_ability() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface* method), 63
- persist\_ability() (*app.service.rest\_svc.RestService* method), 70
- persist\_adversary() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface* method), 63
- persist\_adversary() (*app.service.rest\_svc.RestService* method), 70
- persist\_source() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface* method), 63
- persist\_source() (*app.service.rest\_svc.RestService* method), 70
- phase\_to\_atomic\_ordering() (*app.objects.c\_adversary.AdversarySchema* method), 53
- pin() (*app.objects.secondclass.c\_link.Link* property), 46
- Planner (class in *app.objects.c\_planner*), 57
- PlannerSchema (class in *app.objects.c\_planner*), 57
- PlanningService (class in *app.service.planning\_svc*), 68
- PlanningServiceInterface (class in *app.service.interfaces.i\_planning\_svc*), 62
- PLATFORM (*app.objects.c\_operation.Operation.Reason* attribute), 55
- Plugin (class in *app.objects.c\_plugin*), 57
- PluginSchema (class in *app.objects.c\_plugin*), 57
- prepare\_link() (*app.objects.secondclass.c\_link.LinkSchema* method), 46
- prepare\_parser() (*app.objects.secondclass.c\_parser.ParserSchema* method), 47
- prepend\_to\_file() (*app.utility.base\_world.BaseWorld* static method), 73
- PRIVILEGE (*app.objects.c\_operation.Operation.Reason* attribute), 55
- privileged\_to\_run() (*app.objects.c\_agent.Agent* method), 54
- PrivilegesSchema (class in *app.utility.base\_world*), 74
- R**
- re\_base64 (*app.utility.base\_world.BaseWorld* attribute), 73

re\_index (*app.utility.base\_planning\_svc.BasePlanningService* static method), 72  
   attribute), 71      remove\_links\_missing\_requirements ()  
 re\_limited (*app.utility.base\_planning\_svc.BasePlanningService* (*app.utility.base\_planning\_svc.BasePlanningService*  
   attribute), 71      method), 72  
 re\_trait (*app.utility.base\_planning\_svc.BasePlanningService* remove\_nones () (*app.objects.secondclass.c\_parserconfig.ParserConfig*  
   attribute), 71      method), 48  
 re\_variable (*app.utility.base\_planning\_svc.BasePlanningService* remove\_nulls () (*app.objects.c\_agent.AgentFieldsSchema*  
   attribute), 71      method), 54  
 read () (in module *app.utility.file\_decryptor*), 74      replace () (*app.objects.c\_agent.Agent* method), 54  
 read\_file () (*app.service.file\_svc.FileSvc* method), 67      replace\_app\_props ()  
   67      (*app.utility.base\_object.BaseObject* method),  
   70  
 read\_file () (*app.service.interfaces.i\_file\_svc.FileServiceInterface* replace\_cleanup () (*app.objects.c\_ability.Ability*  
   method), 61      method), 52  
 read\_result\_file () (*app.service.file\_svc.FileSvc* report () (*app.objects.c\_operation.Operation*  
   method), 67      method), 56  
 read\_result\_file ()  
   (*app.service.interfaces.i\_file\_svc.FileServiceInterface* report () (in module *app.service.contact\_svc*), 65  
   method), 62      Requirement (class in  
 RED (*app.utility.base\_world.BaseWorld.Access* at- *app.objects.secondclass.c\_requirement*),  
   tribute), 73      49  
 refresh () (*app.contacts.contact\_tcp.TcpSessionHandler* RequirementSchema (class in  
   method), 43      *app.objects.secondclass.c\_requirement*,  
   49  
 register () (*app.service.contact\_svc.ContactService* RESERVED (*app.objects.c\_ability.Ability* attribute), 52  
   method), 65      RESERVED (*app.objects.c\_agent.Agent* attribute), 54  
 register () (*app.service.interfaces.i\_contact\_svc.ContactServiceInterface* rest\_core () (*app.api.rest\_api.RestApi* method), 41  
   method), 60      RestApi (class in *app.api.rest\_api*), 41  
 register\_contacts ()  
   (*app.service.app\_svc.AppService* method), 64      restore\_state () (*app.service.data\_svc.DataService*  
   64      method), 66  
 register\_contacts ()  
   (*app.service.interfaces.i\_app\_svc.AppServiceInterface* restore\_state () (*app.service.interfaces.i\_data\_svc.DataServiceInterface*  
   method), 59      method), 61  
   RestService (class in *app.service.rest\_svc*), 69  
 Relationship (class in *app.objects.secondclass.c\_relationship* RestServiceInterface (class in  
   48      *app.service.interfaces.i\_rest\_svc*), 63  
 RelationshipSchema (class in *app.objects.secondclass.c\_relationship* Result (class in *app.objects.secondclass.c\_result*), 49  
   48      ResultSchema (class in  
   *app.objects.secondclass.c\_result*), 49  
 reload\_data () (*app.service.data\_svc.DataService* resume\_operations ()  
   method), 66      (*app.service.app\_svc.AppService* method),  
   64  
 reload\_data () (*app.service.interfaces.i\_data\_svc.DataServiceInterface* resume\_operations ()  
   method), 61      (*app.service.interfaces.i\_app\_svc.AppServiceInterface*  
   method), 59  
 remove () (*app.service.data\_svc.DataService* method), 66      retrieve () (*app.utility.base\_object.BaseObject* static  
   66      method), 71  
 remove () (*app.service.interfaces.i\_data\_svc.DataServiceInterface* method), 71      retrieve\_compiled\_file ()  
   method), 61      (*app.service.app\_svc.AppService* method),  
   64  
 remove\_completed\_links ()  
   (*app.utility.base\_planning\_svc.BasePlanningService* static method), 71      retrieve\_compiled\_file ()  
   71      (*app.service.interfaces.i\_app\_svc.AppServiceInterface*  
   method), 59  
 remove\_links\_above\_visibility ()  
   (*app.utility.base\_planning\_svc.BasePlanningService* static method), 72      retrieve\_config () (*app.contacts.contact\_gist.Gist*  
   static method), 72      method), 42  
 remove\_links\_missing\_facts ()  
   (*app.utility.base\_planning\_svc.BasePlanningService* rule (class in *app.objects.secondclass.c\_rule*), 50  
   static method), 72      50

RuleAction (class in *app.utility.rule\_set*), 75  
 RuleActionField (class in *app.objects.secondclass.c\_rule*), 50  
 RuleSchema (class in *app.objects.secondclass.c\_rule*), 50  
 RuleSet (class in *app.utility.rule\_set*), 75  
 run() (*app.contacts.handles.h\_beacon.Handle* static method), 42  
 run() (*app.objects.c\_operation.Operation* method), 56  
 run() (*app.utility.base\_obfuscator.BaseObfuscator* method), 70  
 run\_scheduler() (*app.service.app\_svc.AppService* method), 64  
 run\_scheduler() (*app.service.interfaces.i\_app\_svc.AppServiceInterface* method), 59

**S**

save\_file() (*app.service.file\_svc.FileSvc* method), 67  
 save\_file() (*app.service.interfaces.i\_file\_svc.FileServiceInterface* method), 62  
 save\_multipart\_file\_upload() (*app.service.file\_svc.FileSvc* method), 67  
 save\_multipart\_file\_upload() (*app.service.interfaces.i\_file\_svc.FileServiceInterface* method), 62  
 save\_state() (*app.service.data\_svc.DataService* method), 66  
 save\_state() (*app.service.interfaces.i\_data\_svc.DataServiceInterface* method), 61  
 Schedule (class in *app.objects.c\_schedule*), 58  
 ScheduleSchema (class in *app.objects.c\_schedule*), 58  
 schema (*app.objects.c\_ability.Ability* attribute), 52  
 schema (*app.objects.c\_adversary.Adversary* attribute), 53  
 schema (*app.objects.c\_agent.Agent* attribute), 54  
 schema (*app.objects.c\_obfuscator.Obfuscator* attribute), 55  
 schema (*app.objects.c\_operation.Operation* attribute), 56  
 schema (*app.objects.c\_planner.Planner* attribute), 57  
 schema (*app.objects.c\_plugin.Plugin* attribute), 57  
 schema (*app.objects.c\_schedule.Schedule* attribute), 58  
 schema (*app.objects.c\_source.Source* attribute), 59  
 schema (*app.objects.secondclass.c\_fact.Fact* attribute), 44  
 schema (*app.objects.secondclass.c\_instruction.Instruction* attribute), 45  
 schema (*app.objects.secondclass.c\_link.Link* attribute), 46  
 schema (*app.objects.secondclass.c\_parser.Parser* attribute), 46  
 schema (*app.objects.secondclass.c\_parserconfig.ParserConfig* attribute), 47  
 schema (*app.objects.secondclass.c\_relationship.Relationship* attribute), 48  
 schema (*app.objects.secondclass.c\_requirement.Requirement* attribute), 49  
 schema (*app.objects.secondclass.c\_result.Result* attribute), 49  
 schema (*app.objects.secondclass.c\_rule.Rule* attribute), 50  
 schema (*app.objects.secondclass.c\_variation.Variation* attribute), 50  
 schema (*app.objects.secondclass.c\_visibility.Visibility* attribute), 71  
 schema (*app.utility.base\_object.BaseObject* attribute), 71  
 score() (*app.objects.secondclass.c\_visibility.Visibility* property), 51  
 send() (*app.contacts.contact\_tcp.TcpSessionHandler* method), 43  
 set\_config() (*app.utility.base\_world.BaseWorld* static method), 74  
 set\_start\_details() (*app.objects.c\_operation.Operation* method), 56  
 set\_value() (*app.utility.base\_parser.BaseParser* static method), 71  
 sort\_links() (*app.service.interfaces.i\_planning\_svc.PlanningServiceInterface* static method), 62  
 sort\_links() (*app.service.planning\_svc.PlanningService* static method), 69  
 Source (class in *app.objects.c\_source*), 58  
 SourceSchema (class in *app.objects.c\_source*), 59  
 start() (*app.contacts.contact\_gist.Gist* method), 42  
 start() (*app.contacts.contact\_html.Html* method), 43  
 start() (*app.contacts.contact\_http.Http* method), 43  
 start() (*app.contacts.contact\_tcp.Tcp* method), 43  
 start() (*app.contacts.contact\_udp.Udp* method), 43  
 start() (*app.contacts.contact\_websocket.WebSocket* method), 43  
 start\_sniffer\_untrusted\_agents() (*app.service.app\_svc.AppService* method), 64  
 start\_sniffer\_untrusted\_agents() (*app.service.interfaces.i\_app\_svc.AppServiceInterface* method), 60  
 states() (*app.objects.c\_operation.Operation* property), 56  
 states() (*app.objects.secondclass.c\_link.Link* property), 46  
 store() (*app.objects.c\_ability.Ability* method), 52  
 store() (*app.objects.c\_adversary.Adversary* method), 53  
 store() (*app.objects.c\_agent.Agent* method), 54



store() (*app.objects.c\_obfuscator.Obfuscator method*), 55  
 store() (*app.objects.c\_operation.Operation method*), 56  
 store() (*app.objects.c\_planner.Planner method*), 57  
 store() (*app.objects.c\_plugin.Plugin method*), 57  
 store() (*app.objects.c\_schedule.Schedule method*), 58  
 store() (*app.objects.c\_source.Source method*), 59  
 store() (*app.objects.interfaces.i\_object.FirstClassObjectInterface method*), 44  
 store() (*app.service.data\_svc.DataService method*), 66  
 store() (*app.service.interfaces.i\_data\_svc.DataServiceInterface method*), 61  
 strip\_yaml() (*app.utility.base\_world.BaseWorld static method*), 74

## T

task() (*app.objects.c\_agent.Agent method*), 54  
 task\_agent\_with\_ability() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface method*), 63  
 task\_agent\_with\_ability() (*app.service.rest\_svc.RestService method*), 70  
 Tcp (*class in app.contacts.contact\_tcp*), 43  
 TcpSessionHandler (*class in app.contacts.contact\_tcp*), 43  
 teardown() (*app.service.app\_svc.AppService method*), 64  
 teardown() (*app.service.interfaces.i\_app\_svc.AppServiceInterface method*), 60  
 test() (*app.objects.c\_ability.Ability property*), 52  
 trait() (*app.objects.c\_source.Adjustment property*), 58  
 trim\_links() (*app.utility.base\_planning\_svc.BasePlanningService method*), 72

## U

Udp (*class in app.contacts.contact\_udp*), 43  
 unique() (*app.objects.c\_ability.Ability property*), 52  
 unique() (*app.objects.c\_adversary.Adversary property*), 53  
 unique() (*app.objects.c\_agent.Agent property*), 54  
 unique() (*app.objects.c\_obfuscator.Obfuscator property*), 55  
 unique() (*app.objects.c\_operation.Operation property*), 56  
 unique() (*app.objects.c\_planner.Planner property*), 57  
 unique() (*app.objects.c\_plugin.Plugin property*), 57  
 unique() (*app.objects.c\_schedule.Schedule property*), 58  
 unique() (*app.objects.c\_source.Source property*), 59  
 unique() (*app.objects.interfaces.i\_object.FirstClassObjectInterface property*), 44  
 unique() (*app.objects.secondclass.c\_fact.Fact property*), 44  
 unique() (*app.objects.secondclass.c\_link.Link property*), 46  
 unique() (*app.objects.secondclass.c\_parser.Parser property*), 46  
 unique() (*app.objects.secondclass.c\_relationship.Relationship property*), 48  
 unique() (*app.objects.secondclass.c\_requirement.Requirement property*), 49  
 unknown (*app.objects.secondclass.c\_link.LinkSchema.Meta attribute*), 46  
 unknown (*app.objects.secondclass.c\_parserconfig.ParserConfigSchema.Meta attribute*), 47  
 UNTRUSTED (*app.objects.c\_operation.Operation.Reason attribute*), 55  
 update() (*app.utility.base\_object.BaseObject method*), 71  
 update\_agent\_data() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface method*), 63  
 update\_agent\_data() (*app.service.rest\_svc.RestService method*), 70  
 update\_chain\_data() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface method*), 63  
 update\_chain\_data() (*app.service.rest\_svc.RestService method*), 70  
 update\_config() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface method*), 63  
 update\_config() (*app.service.rest\_svc.RestService method*), 70  
 update\_operation() (*app.objects.c\_operation.Operation method*), 56  
 update\_operation() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface method*), 63  
 update\_operation() (*app.service.rest\_svc.RestService method*), 70  
 update\_planner() (*app.service.interfaces.i\_rest\_svc.RestServiceInterface method*), 63  
 update\_planner() (*app.service.rest\_svc.RestService method*), 70  
 update\_stopping\_condition\_met() (*app.service.planning\_svc.PlanningService method*), 69  
 upload\_file() (*app.api.rest\_api.RestApi method*), 41

User (*app.utility.base\_world.BaseWorld.Privileges* attribute), 73  
 xor\_file() (*in module app.utility.payload\_encoder*), 74  
 username() (*app.service.auth\_svc.AuthService.User* property), 65

## V

valid\_config() (*app.contacts.contact\_gist.Gist* method), 42  
 validate\_login() (*app.api.rest\_api.RestApi* method), 42  
 validate\_requirement() (*app.service.app\_svc.AppService* method), 64  
 validate\_requirements() (*app.service.app\_svc.AppService* method), 64  
 value() (*app.objects.c\_source.Adjustment* property), 58  
 Variation (class *in app.objects.secondclass.c\_variation*), 50  
 VariationSchema (class *in app.objects.secondclass.c\_variation*), 50  
 Visibility (class *in app.objects.secondclass.c\_visibility*), 51  
 VisibilitySchema (class *in app.objects.secondclass.c\_visibility*), 51

## W

wait\_for\_completion() (*app.objects.c\_operation.Operation* method), 56  
 wait\_for\_links\_completion() (*app.objects.c\_operation.Operation* method), 56  
 walk\_file\_path() (*app.utility.base\_world.BaseWorld* static method), 74  
 WebSocket (class *in app.contacts.contact\_websocket*), 43  
 which\_plugin() (*app.objects.c\_ability.Ability* method), 52  
 which\_plugin() (*app.objects.c\_adversary.Adversary* method), 53  
 which\_plugin() (*app.objects.c\_planner.Planner* method), 57  
 write\_result\_file() (*app.service.file\_svc.FileSvc* method), 67  
 write\_result\_file() (*app.service.interfaces.i\_file\_svc.FileServiceInterface* method), 62

## X

xor\_bytes() (*in module app.utility.payload\_encoder*), 74